# NAG Fortran Library Routine Document C05PCF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

# 1 Purpose

C05PCF is a comprehensive routine to find a solution of a system of nonlinear equations by a modification of the Powell hybrid method. The user must provide the Jacobian.

# 2 Specification

```
SUBROUTINE CO5PCF(FCN, N, X, FVEC, FJAC, LDFJAC, XTOL, MAXFEV, DIAG,

MODE, FACTOR, NPRINT, NFEV, NJEV, R, LR, QTF, W,

IFAIL)

INTEGER

N, LDFJAC, MAXFEV, MODE, NPRINT, NFEV, NJEV, LR, IFAIL

real

X(N), FVEC(N), FJAC(LDFJAC,N), XTOL, DIAG(N), FACTOR,

R(LR), QTF(N), W(N,4)

EXTERNAL

FCN
```

# 3 Description

The system of equations is defined as:

$$f_i(x_1, x_2, \dots, x_n) = 0$$
, for  $i = 1, 2, \dots, n$ .

C05PCF is based upon the MINPACK routine HYBRJ (Moré *et al.* (1980)). It chooses the correction at each step as a convex combination of the Newton and scaled gradient directions. Under reasonable conditions this guarantees global convergence from starting points far from the solution and a fast rate of convergence. The Jacobian is updated by the rank-1 method of Broyden. At the starting point the Jacobian is calculated, but it is not recalculated until the rank-1 method fails to produce satisfactory progress. For more details see Powell (1970).

## 4 References

Moré J J, Garbow B S and Hillstrom K E (1980) User guide for MINPACK-1 *Technical Report ANL-80-74* Argonne National Laboratory

Powell M J D (1970) A hybrid method for nonlinear algebraic equations *Numerical Methods for Nonlinear Algebraic Equations* (ed P Rabinowitz) Gordon and Breach

## 5 Parameters

1: FCN – SUBROUTINE, supplied by the user.

External Procedure

Depending upon the value of IFLAG, FCN must either return the values of the functions  $f_i$  at a point x or return the Jacobian at x.

Its specification is:

```
SUBROUTINE FCN(N, X, FVEC, FJAC, LDFJAC, IFLAG)
INTEGER N, LDFJAC, IFLAG
real X(N), FVEC(N), FJAC(LDFJAC,N)

1: N - INTEGER

On entry: the number of equations, n.
```

[NP3546/20A] C05PCF.1

# 2: X(N) - real array

Input

On entry: the components of the point at which the functions or the Jacobian must be evaluated.

# 3: FVEC(N) - real array

Output

On exit: if IFLAG = 1 on entry, FVEC must contain the function values  $f_i(x)$  (unless IFLAG is set to a negative value by FCN).

If IFLAG = 0 or 2 on entry, FVEC must not be changed.

## 4: FJAC(LDFJAC,N) – *real* array

Output

On exit: if IFLAG = 2 on entry, FJAC(i,j) must contain the value of  $\frac{\partial f_i}{\partial x_j}$  at the point x, for  $i,j=1,2,\ldots,n$  (unless IFLAG is set to a negative value by FCN).

If IFLAG = 0 or 1 on entry, FJAC must not be changed.

## 5: LDFJAC – INTEGER

Input

On entry: the first dimension of FJAC.

#### 6: IFLAG – INTEGER

Input/Output

On entry: IFLAG = 0, 1 or 2:

if IFLAG = 0, X and FVEC are available for printing (see NPRINT below);

if IFLAG = 1, FVEC is to be updated;

if IFLAG = 2, FJAC is to be updated.

*On exit*: in general, IFLAG should not be reset by FCN. If, however, the user wishes to terminate execution (perhaps because some illegal point X has been reached), then IFLAG should be set to a negative integer. This value will be returned through IFAIL.

FCN must be declared as EXTERNAL in the (sub)program from which C05PCF is called. Parameters denoted as *Input* must **not** be changed by this procedure.

# 2: N-INTEGER

Input

On entry: the number of equations, n.

Constraint: N > 0.

# 3: X(N) - real array

Input/Output

On entry: an initial guess at the solution vector.

On exit: the final estimate of the solution vector.

## 4: FVEC(N) - real array

Output

On exit: the function values at the final point, X.

## 5: FJAC(LDFJAC,N) – *real* array

Output

On exit: the orthogonal matrix Q produced by the QR factorization of the final approximate Jacobian.

## 6: LDFJAC – INTEGER

Input

On entry: the first dimension of the array FJAC as declared in the (sub)program from which C05PCF is called.

Constraint: LDFJAC  $\geq N$ .

C05PCF.2 [NP3546/20A]

C05PCF

7: XTOL – real Input

On entry: the accuracy in X to which the solution is required.

Suggested value: the square root of the machine precision.

Constraint:  $XTOL \ge 0.0$ .

## 8: MAXFEV – INTEGER

Input

On entry: the maximum number of calls to FCN with IFLAG  $\neq$  0. C05PCF will exit with IFAIL = 2, if, at the end of an iteration, the number of calls to FCN exceeds MAXFEV.

Suggested value: MAXFEV =  $100 \times (N + 1)$ .

Constraint: MAXFEV > 0.

## 9: DIAG(N) – *real* array

Input/Output

On entry: if MODE = 2 (see below), DIAG must contain multiplicative scale factors for the variables.

Constraint: DIAG(i) > 0.0, for i = 1, 2, ..., n.

On exit: the scale factors actually used (computed internally if MODE  $\neq$  2).

#### 10: MODE - INTEGER

Input

On entry: indicates whether or not the user has provided scaling factors in DIAG. If MODE = 2, the scaling must have been specified in DIAG. Otherwise, the variables will be scaled internally.

11: FACTOR – *real* 

Input

On entry: a quantity to be used in determining the initial step bound. In most cases, FACTOR should lie between 0.1 and 100.0. (The step bound is FACTOR  $\times$  ||DIAG  $\times$  X||<sub>2</sub> if this is non-zero; otherwise the bound is FACTOR.)

Suggested value: FACTOR = 100.0.

Constraint: FACTOR > 0.0.

## 12: NPRINT – INTEGER

Input

On entry: indicates whether or not special calls to FCN with IFLAG = 0 are to be made for printing purposes. If NPRINT  $\leq$  0, then no calls are made. If NPRINT > 0, then FCN is called at the beginning of the first iteration, every NPRINT iterations thereafter and immediately prior to the return from C05PCF.

## 13: NFEV – INTEGER

Output

On exit: the number of calls made to FCN to evaluate the functions.

## 14: NJEV – INTEGER

Output

On exit: the number of calls made to FCN to evaluate the Jacobian.

# 15: R(LR) - real array

Output

On exit: the upper triangular matrix R produced by the QR factorization of the final approximate Jacobian, stored row-wise.

## 16: LR – INTEGER

Input

On entry: the dimension of the array R.

Constraint: LR  $\geq$  N  $\times$  (N + 1)/2.

[NP3546/20A] C05PCF.3

17: QTF(N) - real array Output

On exit: the vector  $Q^T f$ .

18: W(N,4) - real array Workspace

19: IFAIL – INTEGER Input/Output

On entry: IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.

On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

# 6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

## IFAIL < 0

This indicates an exit from C05PCF because the user has set IFLAG negative in FCN. The value of IFAIL will be the same as the user's setting of IFLAG.

## IFAIL = 1

```
On entry, N \le 0, or XTOL < 0.0, or MAXFEV \le 0, or FACTOR \le 0.0, or LDFJAC < N, or LR < N \times (N+1)/2, or MODE = 2 and DIAG(i) \le 0.0 for some i, i = 1, 2, \dots, N.
```

## IFAIL = 2

There have been MAXFEV evaluations of FCN to evaluate the functions. Consider restarting the calculation from the final point held in X.

# IFAIL = 3

No further improvement in the approximate solution X is possible; XTOL is too small.

## IFAIL = 4

The iteration is not making good progress, as measured by the improvement from the last 5 Jacobian evaluations.

## IFAIL = 5

The iteration is not making good progress, as measured by the improvement from the last 10 iterations.

The values IFAIL = 4 and IFAIL = 5 may indicate that the system does not have a zero, or that the solution is very close to the origin (see Section 7). Otherwise, rerunning C05PCF from a different starting point may avoid the region of difficulty.

C05PCF.4 [NP3546/20A]

# 7 Accuracy

If  $\hat{x}$  is the true solution and D denotes the diagonal matrix whose entries are defined by the array DIAG then C05PCF tries to ensure that

$$||D \times (x - \hat{x})||_2 \leq \text{XTOL} \times ||D \times \hat{x}||_2$$
.

If this condition is satisfied with  $XTOL = 10^{-k}$ , then the larger components of Dx have k significant decimal digits. There is a danger that the smaller components of Dx may have large relative errors, but the fast rate of convergence of C05PCF usually avoids this possibility.

If XTOL is less than the *machine precision* and the above test is satisfied with the *machine precision* in place of XTOL, then the routine exits with IFAIL = 3.

**Note:** this convergence test is based purely on relative error, and may not indicate convergence if the solution is very close to the origin.

The test assumes that the functions and the Jacobian are coded consistently and that the functions are reasonably well behaved. If these conditions are not satisfied then C05PCF may incorrectly indicate convergence. The coding of the Jacobian can be checked using C05ZAF. If the Jacobian is coded correctly, then the validity of the answer can be checked by rerunning C05PCF with a tighter tolerance.

## **8 Further Comments**

The time required by C05PCF to solve a given problem depends on n, the behaviour of the functions, the accuracy requested and the starting point. The number of arithmetic operations executed by C05PCF is about  $11.5 \times n^2$  to process each evaluation of the functions and about  $1.3 \times n^3$  to process each evaluation of the Jacobian. Unless FCN can be evaluated quickly, the timing of C05PCF will be strongly influenced by the time spent in FCN.

Ideally the problem should be scaled so that at the solution the function values are of comparable magnitude.

# 9 Example

To determine the values  $x_1, \ldots, x_9$  which satisfy the tridiagonal equations:

$$(3-2x_1)x_1-2x_2 = -1, -x_{i-1} + (3-2x_i)x_i - 2x_{i+1} = -1, i = 2, 3, \dots, 8 -x_8 + (3-2x_9)x_9 = -1.$$

#### 9.1 Program Text

**Note:** the listing of the example program presented below uses **bold italicised** terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
CO5PCF Example Program Text
Mark 14 Revised. NAG Copyright 1989.
.. Parameters ..
                 N, LDFJAC, LR
INTEGER
                 (N=9,LDFJAC=N,LR=(N*(N+1))/2)
PARAMETER
INTEGER
                 NOUT
PARAMETER
                 (NOUT=6)
.. Local Scalars ..
real
                 FACTOR, FNORM, XTOL
INTEGER
                 IFAIL, J, MAXFEV, MODE, NFEV, NJEV, NPRINT
.. Local Arrays ..
                 DIAG(N), FJAC(LDFJAC,N), FVEC(N), QTF(N), R(LR),
real
                 W(N,4), X(N)
.. External Functions ..
real
                 F06EJF, X02AJF
EXTERNAL
                 FO6EJF, XO2AJF
.. External Subroutines ..
EXTERNAL
         CO5PCF, FCN
.. Intrinsic Functions ..
```

[NP3546/20A] C05PCF.5

```
SQRT
      INTRINSIC
      .. Executable Statements ..
     WRITE (NOUT,*) 'CO5PCF Example Program Results'
      WRITE (NOUT, *)
      The following starting values provide a rough solution.
      DO 20 J = 1, N
         X(J) = -1.0e0
   20 CONTINUE
      XTOL = SQRT(XO2AJF())
     DO 40 J = 1, N
        DIAG(J) = 1.0e0
   40 CONTINUE
      MAXFEV = 1000
     MODE = 2
     FACTOR = 100.0e0
     NPRINT = 0
     IFAIL = 1
     CALL CO5PCF (FCN,N,X,FVEC,FJAC,LDFJAC,XTOL,MAXFEV,DIAG,MODE,FACTOR,
                  NPRINT, NFEV, NJEV, R, LR, QTF, W, IFAIL)
      IF (IFAIL.EQ.O) THEN
         FNORM = FO6EJF(N, FVEC, 1)
         WRITE (NOUT, 99999) 'Final 2-norm of the residuals =', FNORM
         WRITE (NOUT, *)
         WRITE (NOUT, 99998) 'Number of function evaluations =', NFEV
         WRITE (NOUT, *)
         WRITE (NOUT, 99998) 'Number of Jacobian evaluations =', NJEV
         WRITE (NOUT, *)
         WRITE (NOUT,*) 'Final approximate solution'
         WRITE (NOUT, *)
         WRITE (NOUT, 99997) (X(J), J=1, N)
         WRITE (NOUT, 99996) 'IFAIL = ', IFAIL
         IF (IFAIL.GT.2) THEN
            WRITE (NOUT, *)
            WRITE (NOUT,*) 'Approximate solution:'
            WRITE (NOUT,*)
            WRITE (NOUT, 99997) (X(J), J=1, N)
         END IF
     END IF
      STOP
99999 FORMAT (1X,A,e12.4)
99998 FORMAT (1X,A,I10)
99997 FORMAT (1X,3F12.4)
99996 FORMAT (1X,A,I2)
     END
      SUBROUTINE FCN(N,X,FVEC,FJAC,LDFJAC,IFLAG)
      .. Parameters ..
     real
                     ZERO, ONE, TWO, THREE, FOUR
                     (ZERO=0.0e0,ONE=1.0e0,TWO=2.0e0,THREE=3.0e0,
     PARAMETER
                     FOUR=4.0e0)
      .. Scalar Arguments ..
     INTEGER
                     IFLAG, LDFJAC, N
      .. Array Arguments .
     real
                     FJAC(LDFJAC,N), FVEC(N), X(N)
      .. Local Scalars ..
     INTEGER
                     J, K
      .. Executable Statements ..
      IF (IFLAG.EQ.O) THEN
         Insert print statements here when NPRINT is positive.
         RETURN
     ELSE
         IF (IFLAG.NE.2) THEN
            DO 20 K = 1, N
               FVEC(K) = (THREE-TWO*X(K))*X(K) + ONE
               IF (K.GT.1) FVEC(K) = FVEC(K) - X(K-1)
```

C05PCF.6 [NP3546/20A]

```
IF (K.LT.N) FVEC(K) = FVEC(K) - TWO*X(K+1)
20
        CONTINUE
     ELSE
        DO 60 K = 1, N
DO 40 J = 1, N
             FJAC(K,J) = ZERO
40
           CONTINUE
           IF (K.LT.N) FJAC(K,K+1) = -TWO
60
        CONTINUE
     END IF
  END IF
  RETURN
  END
```

# 9.2 Program Data

None.

# 9.3 Program Results

```
CO5PCF Example Program Results
Final 2-norm of the residuals = 0.1193E-07
Number of function evaluations =
                                        11
Number of Jacobian evaluations =
                                         1
Final approximate solution
    -0.5707
                             -0.7017
                -0.6816
    -0.7042
                -0.7014
                            -0.6919
     -0.6658
                -0.5960
                             -0.4164
```

[NP3546/20A] C05PCF.7 (last)