

# NAG Fortran Library Routine Document

## C06HAF

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

### 1 Purpose

C06HAF computes the discrete Fourier sine transforms of  $m$  sequences of real data values. This routine is designed to be particularly efficient on vector processors.

### 2 Specification

```
SUBROUTINE C06HAF(M, N, X, INIT, TRIG, WORK, IFAIL)
INTEGER          M, N, IFAIL
real           X(M*N), TRIG(2*N), WORK(M*N)
CHARACTER*1      INIT
```

### 3 Description

Given  $m$  sequences of  $n-1$  real data values  $x_j^p$ , for  $j = 1, 2, \dots, n-1$ ;  $p = 1, 2, \dots, m$ , this routine simultaneously calculates the Fourier sine transforms of all the sequences defined by:

$$\hat{x}_k^p = \sqrt{\frac{2}{n}} \sum_{j=1}^{n-1} x_j^p \times \sin\left(jk\frac{\pi}{n}\right), \quad k = 1, 2, \dots, n-1; \quad p = 1, 2, \dots, m.$$

(Note the scale factor  $\sqrt{\frac{2}{n}}$  in this definition.)

The Fourier sine transform defined above is its own inverse, and two consecutive calls of this routine with the same data will restore the original data.

The transform calculated by this routine can be used to solve Poisson's equation when the solution is specified at both left and right boundaries (Swarztrauber (1977)). (See the C06 Chapter Introduction.)

The routine uses a variant of the fast Fourier transform (FFT) algorithm (Brigham (1974)) known as the Stockham self-sorting algorithm, described in Temperton (1983a), together with pre- and post-processing stages described in Swarztrauber (1982). Special coding is provided for the factors 2, 3, 4, 5 and 6. This routine is designed to be particularly efficient on vector processors, and it becomes especially fast as  $m$ , the number of transforms to be computed in parallel, increases.

### 4 References

Brigham E O (1974) *The Fast Fourier Transform* Prentice-Hall

Swarztrauber P N (1977) The methods of cyclic reduction, Fourier analysis and the FACR algorithm for the discrete solution of Poisson's equation on a rectangle *SIAM Rev.* **19** (3) 490–501

Swarztrauber P N (1982) Vectorizing the FFT's *Parallel Computation* (ed G Rodrigue) 51–83 Academic Press

Temperton C (1983a) Fast mixed-radix real Fourier transforms *J. Comput. Phys.* **52** 340–350

### 5 Parameters

1: M – INTEGER

*Input*

*On entry:* the number of sequences to be transformed,  $m$ .

*Constraint:*  $M \geq 1$ .

- 2: N – INTEGER Input
- On entry:* one more than the number of real values in each sequence, i.e., the number of values in each sequence is  $n - 1$ .
- Constraint:*  $N \geq 1$ .
- 3: X(M\*N) – *real* array Input/Output
- On entry:* the data must be stored in X as if in a two-dimensional array of dimension  $(1 : M, 1 : N)$ ; each of the  $m$  sequences is stored in a **row** of the array. In other words, if the  $n - 1$  data values of the  $p$ th sequence to be transformed are denoted by  $x_j^p$ , for  $j = 1, 2, \dots, n - 1$ ;  $p = 1, 2, \dots, m$ , then the first  $m(n - 1)$  elements of the array X must contain the values
- $$x_1^1, x_1^2, \dots, x_1^m, x_2^1, x_2^2, \dots, x_2^m, \dots, x_{n-1}^1, x_{n-1}^2, \dots, x_{n-1}^m.$$
- The  $n$ th element of each row  $x_n^p$ , for  $p = 1, 2, \dots, m$ , is required as workspace. These  $m$  elements may contain arbitrary values on entry, and are set to zero by the routine.
- On exit:* the  $m$  Fourier transforms stored as if in a two-dimensional array of dimension  $(1 : M, 1 : N)$ . Each of the  $m$  transforms is stored in a **row** of the array, overwriting the corresponding original sequence. If the  $n - 1$  components of the  $p$ th Fourier sine transform are denoted by  $\hat{x}_k^p$ , for  $k = 1, 2, \dots, n - 1$ ;  $p = 1, 2, \dots, m$ , then the  $mn$  elements of the array X contain the values
- $$\hat{x}_1^1, \hat{x}_1^2, \dots, \hat{x}_1^m, \hat{x}_2^1, \hat{x}_2^2, \dots, \hat{x}_2^m, \dots, \hat{x}_{n-1}^1, \hat{x}_{n-1}^2, \dots, \hat{x}_{n-1}^m, 0, 0, \dots, 0 \text{ (} m \text{ times)}.$$
- If  $n = 1$ , the  $m$  elements of X are set to zero.
- 4: INIT – CHARACTER\*1 Input
- On entry:* if the trigonometric coefficients required to compute the transforms are to be calculated by the routine and stored in the array TRIG, then INIT must be set equal to 'I' (Initial call).
- If INIT contains 'S' (Subsequent call), then the routine assumes that trigonometric coefficients for the specified value of  $n$  are supplied in the array TRIG, having been calculated in a previous call to one of C06HAF, C06HBF, C06HCF or C06HDF.
- If INIT contains 'R' (Restart), then the routine assumes that trigonometric coefficients for the particular value of  $n$  are supplied in the array TRIG, but does not check that C06HAF, C06HBF, C06HCF or C06HDF have previously been called. This option allows the TRIG array to be stored in an external file, read in and re-used without the need for a call with INIT equal to 'I'. The routine carries out a simple test to check that the current value of  $n$  is consistent with the array TRIG.
- Constraint:* INIT = 'I', 'S' or 'R'.
- 5: TRIG(2\*N) – *real* array Input/Output
- On entry:* if INIT = 'S' or 'R', TRIG must contain the required coefficients calculated in a previous call of the routine. Otherwise TRIG need not be set.
- On exit:* TRIG contains the required coefficients (computed by the routine if INIT = 'I').
- 6: WORK(M\*N) – *real* array Workspace
- 7: IFAIL – INTEGER Input/Output
- On entry:* IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.
- On exit:* IFAIL = 0 unless the routine detects an error (see Section 6).
- For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**

## 6 Error Indicators and Warnings

If on entry  $IFAIL = 0$  or  $-1$ , explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

$IFAIL = 1$

On entry,  $M < 1$ .

$IFAIL = 2$

On entry,  $N < 1$ .

$IFAIL = 3$

On entry, INIT is not one of 'I', 'S' or 'R'.

$IFAIL = 4$

Not used at this Mark.

$IFAIL = 5$

On entry, INIT = 'S' or 'R', but the array TRIG and the current value of N are inconsistent.

$IFAIL = 6$

## 7 Accuracy

Some indication of accuracy can be obtained by performing a subsequent inverse transform and comparing the results with the original sequence (in exact arithmetic they would be identical).

## 8 Further Comments

The time taken by the routine is approximately proportional to  $nm \times \log n$ , but also depends on the factors of  $n$ . The routine is fastest if the only prime factors of  $n$  are 2, 3 and 5, and is particularly slow if  $n$  is a large prime, or has large prime factors.

## 9 Example

This program reads in sequences of real data values and prints their Fourier sine transforms (as computed by C06HAF). It then calls C06HAF again and prints the results which may be compared with the original sequence.

### 9.1 Program Text

**Note:** the listing of the example program presented below uses *bold italicised* terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
*      C06HAF Example Program Text
*      Mark 14 Revised.  NAG Copyright 1989.
*      .. Parameters ..
      INTEGER          NIN, NOUT
      PARAMETER        (NIN=5,NOUT=6)
      INTEGER          MMAX, NMAX
      PARAMETER        (MMAX=5,NMAX=20)
*      .. Local Scalars ..
      INTEGER          I, IFAIL, J, M, N
*      .. Local Arrays ..
      real              TRIG(2*NMAX), WORK(MMAX*NMAX), X(NMAX*MMAX)
*      .. External Subroutines ..
```

```

      EXTERNAL          C06HAF
*      .. Executable Statements ..
      WRITE (NOUT,*) 'C06HAF Example Program Results'
*      Skip heading in data file
      READ (NIN,*)
20    READ (NIN,*,END=120) M, N
      IF (M.LE.MMAX .AND. N.LE.NMAX) THEN
        DO 40 J = 1, M
          READ (NIN,*) (X((I-1)*M+J),I=1,N-1)
40      CONTINUE
        WRITE (NOUT,*)
        WRITE (NOUT,*) 'Original data values'
        WRITE (NOUT,*)
        DO 60 J = 1, M
          WRITE (NOUT,99999) (X((I-1)*M+J),I=1,N-1)
60      CONTINUE
        IFAIL = 0
*
*      Compute transform
        CALL C06HAF(M,N,X,'Initial',TRIG,WORK,IFAIL)
*
        WRITE (NOUT,*)
        WRITE (NOUT,*) 'Discrete Fourier sine transforms'
        WRITE (NOUT,*)
        DO 80 J = 1, M
          WRITE (NOUT,99999) (X((I-1)*M+J),I=1,N-1)
80      CONTINUE
*
*      Compute inverse transform
        CALL C06HAF(M,N,X,'Subsequent',TRIG,WORK,IFAIL)
*
        WRITE (NOUT,*)
        WRITE (NOUT,*) 'Original data as restored by inverse transform'
        WRITE (NOUT,*)
        DO 100 J = 1, M
          WRITE (NOUT,99999) (X((I-1)*M+J),I=1,N-1)
100     CONTINUE
        GO TO 20
      ELSE
        WRITE (NOUT,*) 'Invalid value of M or N'
      END IF
120  STOP
*
99999 FORMAT (6X,6F10.4)
      END

```

## 9.2 Program Data

C06HAF Example Program Data

3 6 : Number of sequences, M, (number of values in each sequence)+1, N  
 0.6772 0.1138 0.6751 0.6362 0.1424 : X, sequence 1  
 0.2983 0.1181 0.7255 0.8638 0.8723 : X, sequence 2  
 0.0644 0.6037 0.6430 0.0428 0.4815 : X, sequence 3

## 9.3 Program Results

C06HAF Example Program Results

Original data values

0.6772	0.1138	0.6751	0.6362	0.1424
0.2983	0.1181	0.7255	0.8638	0.8723
0.0644	0.6037	0.6430	0.0428	0.4815

Discrete Fourier sine transforms

1.0014	0.0062	0.0834	0.5286	0.2514
1.2477	-0.6599	0.2570	0.0858	0.2658
0.8521	0.0719	-0.0561	-0.4890	0.2056

Original data as restored by inverse transform

0.6772	0.1138	0.6751	0.6362	0.1424
0.2983	0.1181	0.7255	0.8638	0.8723
0.0644	0.6037	0.6430	0.0428	0.4815

---