NAG Fortran Library Routine Document D02C.IF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

1 Purpose

D02CJF integrates a system of first-order ordinary differential equations over a range with suitable initial conditions, using a variable-order, variable-step Adams method until a user-specified function, if supplied, of the solution is zero, and returns the solution at points specified by the user, if desired.

2 Specification

```
SUBROUTINE DO2CJF(X, XEND, N, Y, FCN, TOL, RELABS, OUTPUT, G, W, IFAIL)

INTEGER

N, IFAIL

Y, XEND, Y(N), TOL, G, W(28+21*N)

CHARACTER*1

EXTERNAL

FCN, OUTPUT, G
```

3 Description

The routine advances the solution of a system of ordinary differential equations

$$y'_i = f_i(x, y_1, y_2, \dots, y_n), \quad i = 1, 2, \dots, n,$$

from x=X to x=XEND using a variable-order, variable-step Adams method. The system is defined by a subroutine FCN supplied by the user, which evaluates f_i in terms of x and y_1, y_2, \ldots, y_n . The initial values of y_1, y_2, \ldots, y_n must be given at x=X.

The solution is returned via the user-supplied routine OUTPUT at points specified by the user, if desired: this solution is obtained by C^1 interpolation on solution values produced by the method. As the integration proceeds a check can be made on the user-specified function g(x,y) to determine an interval where it changes sign. The position of this sign change is then determined accurately by C^1 interpolation to the solution. It is assumed that g(x,y) is a continuous function of the variables, so that a solution of g(x,y)=0.0 can be determined by searching for a change in sign in g(x,y). The accuracy of the integration, the interpolation and, indirectly, of the determination of the position where g(x,y)=0.0, is controlled by the parameters TOL and RELABS.

For a description of Adams methods and their practical implementation see Hall and Watt (1976).

4 References

Hall G and Watt J M (ed.) (1976) Modern Numerical Methods for Ordinary Differential Equations Clarendon Press, Oxford

5 Parameters

1: X - real Input/Output

On entry: the initial value of the independent variable x.

Constraint: $X \neq XEND$.

On exit: if g is supplied by the user, it contains the point where g(x,y) = 0.0, unless $g(x,y) \neq 0.0$ anywhere on the range X to XEND, in which case, X will contain XEND. If g is not supplied by the user it contains XEND, unless an error has occurred, when it contains the value of x at the error.

2: XEND – real Input

On entry: the final value of the independent variable. If XEND < X, integration will proceed in the negative direction.

Constraint: XEND \neq X.

3: N – INTEGER Input

On entry: the number of differential equations.

Constraint: $N \ge 1$.

4: Y(N) - real array Input/Output

On entry: the initial values of the solution y_1, y_2, \dots, y_n at x = X.

On exit: the computed values of the solution at the final point x = X.

5: FCN – SUBROUTINE, supplied by the user.

External Procedure

FCN must evaluate the functions f_i (i.e., the derivatives y_i') for given values of its arguments x, y_1, \dots, y_n .

Its specification is:

SUBROUTINE FCN(X, Y, F)

real X, Y(n), F(n)

where n is the actual value of N in the call of D02CJF.

1: X - real Input

On entry: the value of the independent variable x.

2: Y(n) - real array Input

On entry: the value of the variable y_i , for i = 1, 2, ..., n.

3: F(n) - real array Output

On exit: the value of f_i , for i = 1, 2, ..., n.

FCN must be declared as EXTERNAL in the (sub)program from which D02CJF is called. Parameters denoted as *Input* must **not** be changed by this procedure.

6: TOL – real Input

On entry: a **positive** tolerance for controlling the error in the integration. Hence TOL affects the determination of the position where g(x,y) = 0.0, if g is supplied.

D02CJF has been designed so that, for most problems, a reduction in TOL leads to an approximately proportional reduction in the error in the solution. However, the actual relation between TOL and the accuracy achieved cannot be guaranteed. The user is strongly recommended to call D02CJF with more than one value for TOL and to compare the results obtained to estimate their accuracy. In the absence of any prior knowledge, the user might compare the results obtained by calling D02CJF with TOL = 10.0^{-p} and TOL = 10.0^{-p-1} where p correct decimal digits are required in the solution.

Constraint: TOL > 0.0.

7: RELABS – CHARACTER*1

Input

On entry: the type of error control. At each step in the numerical solution an estimate of the local error, EST, is made. For the current step to be accepted the following condition must be satisfied:

D02CJF.2 [NP3546/20A]

EST =
$$\sqrt{\sum_{i=1}^{n} (e_i/(\tau_r \times |y_i| + \tau_a))^2} \le 1.0$$

where τ_r and τ_a are defined by

RELABS $ au_a$	$ au_r$
'M' TOL	TOL
'A' TOL	0.0
'R' ϵ	TOL
'D' TOL	TOL

where ϵ is a small machine-dependent number and e_i is an estimate of the local error at y_i , computed internally. If the appropriate condition is not satisfied, the step size is reduced and the solution is recomputed on the current step. If the user wishes to measure the error in the computed solution in terms of the number of correct decimal places, then RELABS should be set to 'A' on entry, whereas if the error requirement is in terms of the number of correct significant digits, then RELABS should be set to 'R'. If the user prefers a mixed error test, then RELABS should be set to 'M', otherwise if the user has no preference, RELABS should be set to the default 'D'. Note that in this case 'D' is taken to be 'M'.

Constraint: RELABS = 'M', 'A', 'R', 'D'.

8: OUTPUT – SUBROUTINE, supplied by the user.

External Procedure

OUTPUT permits access to intermediate values of the computed solution (for example to print or plot them), at successive user-specified points. It is initially called by D02CJF with XSOL=X (the initial value of x). The user must reset XSOL to the next point (between the current XSOL and XEND) where OUTPUT is to be called, and so on at each call to OUTPUT. If, after a call to OUTPUT, the reset point XSOL is beyond XEND, D02CJF will integrate to XEND with no further calls to OUTPUT; if a call to OUTPUT is required at the point XSOL=XEND, then XSOL must be given precisely the value XEND.

Its specification is:

SUBROUTINE OUTPUT(XSOL, Y)

real XSOL, Y(n)

where n is the actual value of N in the call of D02CJF.

1: XSOL – real Input/Output

On entry: the output value of the independent variable x.

On exit: the user must set XSOL to the next value of x at which OUTPUT is to be called.

2: Y(n) - real array Input

On entry: the computed solution at the point XSOL.

OUTPUT must be declared as EXTERNAL in the (sub)program from which D02CJF is called. Parameters denoted as *Input* must **not** be changed by this procedure.

If the user does not wish to access intermediate output, the actual argument OUTPUT **must** be the dummy routine D02CJX. (D02CJX is included in the NAG Fortran Library and so need not be supplied by the user. The name may be implementation-dependent: see the Users' Note for your implementation for details.)

9: G - real FUNCTION, supplied by the user.

External Procedure

G must evaluate the function g(x,y) for specified values x,y. It specifies the function g for which the first position x where g(x,y)=0 is to be found.

Its specification is:

where n is the actual value of N in the call of D02CJF.

1: X - real Input

On entry: the value of the independent variable x.

2: Y(n) - real array Input

On entry: the value of the variable y_i , for i = 1, 2, ..., n.

G must be declared as EXTERNAL in the (sub)program from which D02CJF is called. Parameters denoted as *Input* must **not** be changed by this procedure.

If the user does not require the root finding option, the actual argument G **must** be the dummy routine D02CJW. (D02CJW is included in the NAG Fortran Library and so need not be supplied by the user. The name may be implementation-dependent: see the the Users' Note for your implementation for details.)

10: W(28+21*N) - real array

Workspace

11: IFAIL – INTEGER

Input/Output

On entry: IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.

On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

```
On entry, TOL \le 0.0,
or N \le 0,
or RELABS \ne 'M', 'A', 'R' or 'D',
or X = XEND.
```

D02CJF.4 [NP3546/20A]

IFAIL = 2

With the given value of TOL, no further progress can be made across the integration range from the current point x = X. (See Section 8 for a discussion of this error exit.) The components Y(1),Y(2),...,Y(N) contain the computed values of the solution at the current point x = X. If the user has supplied g, then no point at which g(x,y) changes sign has been located up to the point x = X.

IFAIL = 3

TOL is too small for D02CJF to take an initial step. X and Y(1),Y(2),...,Y(N) retain their initial values

IFAIL = 4

XSOL has not been reset or XSOL lies behind X in the direction of integration, after the initial call to OUTPUT, if the OUTPUT option was selected.

IFAIL = 5

A value of XSOL returned by OUTPUT has not been reset or lies behind the last value of XSOL in the direction of integration, if the OUTPUT option was selected.

IFAIL = 6

At no point in the range X to XEND did the function g(x, y) change sign, if g was supplied. It is assumed that g(x, y) = 0 has no solution.

IFAIL = 7

A serious error has occurred in an internal call. Check all subroutine calls and array sizes. Seek expert help.

7 Accuracy

The accuracy of the computation of the solution vector Y may be controlled by varying the local error tolerance TOL. In general, a decrease in local error tolerance should lead to an increase in accuracy. Users are advised to choose RELABS = 'M' unless they have a good reason for a different choice.

If the problem is a root-finding one, then the accuracy of the root determined will depend on the properties of g(x, y). The user should try to code G without introducing any unnecessary cancellation errors.

8 Further Comments

If more than one root is required then D02QFF should be used.

If the routine fails with IFAIL = 3, then it can be called again with a larger value of TOL if this has not already been tried. If the accuracy requested is really needed and cannot be obtained with this routine, the system may be very stiff (see below) or so badly scaled that it cannot be solved to the required accuracy.

If the routine fails with IFAIL = 2, it is probable that it has been called with a value of TOL which is so small that a solution cannot be obtained on the range X to XEND. This can happen for well-behaved systems and very small values of TOL. The user should, however, consider whether there is a more fundamental difficulty. For example:

- (a) in the region of a singularity (infinite value) of the solution, the routine will usually stop with IFAIL = 2, unless overflow occurs first. Numerical integration cannot be continued through a singularity, and analytic treatment should be considered;
- (b) for 'stiff' equations where the solution contains rapidly decaying components, the routine will use very small steps in x (internally to D02CJF) to preserve stability. This will exhibit itself by making the computing time excessively long, or occasionally by an exit with IFAIL = 2. Adams methods are not efficient in such cases, and the user should try D02EJF.

9 Example

We illustrate the solution of four different problems. In each case the differential system (for a projectile) is

$$y' = \tan \phi$$

$$v' = \frac{-0.032 \tan \phi}{v} - \frac{0.02v}{\cos \phi}$$

$$\phi' = \frac{-0.032}{2}$$

over an interval X = 0.0 to XEND = 10.0 starting with values y = 0.5, v = 0.5 and $\phi = \pi/5$. We solve each of the following problems with local error tolerances 1.0E-4 and 1.0E-5.

- (i) To integrate to x = 10.0 producing output at intervals of 2.0 until a point is encountered where y = 0.0.
- (ii) As (i) but with no intermediate output.
- (iii) As (i) but with no termination on a root-finding condition.
- (iv) As (i) but with no intermediate output and no root-finding termination condition.

9.1 Program Text

Note: the listing of the example program presented below uses **bold italicised** terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
DO2CJF Example Program Text
Mark 14 Revised. NAG Copyright 1989.
.. Parameters ..
INTEGER
                 NOUT
                 (NOUT=6)
PARAMETER
INTEGER
               N, IW
PARAMETER
                (N=3,IW=21*N+28)
.. Scalars in Common ..
                 H, XEND
real
INTEGER
                 K
.. Local Scalars ..
               PI, TOL, X
real
INTEGER
                 I, IFAIL, J
.. Local Arrays ..
                 W(IW), Y(N)
.. External Functions ..
real
                 D02CJW, G, X01AAF
EXTERNAL
                 DO2CJW, G, X01AAF
.. External Subroutines ..
EXTERNAL
                DO2CJF, DO2CJX, FCN, OUT
.. Intrinsic Functions ..
INTRINSIC
                real
.. Common blocks ..
COMMON
                 XEND, H, K
.. Executable Statements ..
WRITE (NOUT,*) 'D02CJF Example Program Results'
XEND = 10.0e0
PI = X01AAF(0.0e0)
WRITE (NOUT, *)
WRITE (NOUT, *)
               'Case 1: intermediate output, root-finding'
DO 20 J = 4, 5
   TOL = 10.0e0**(-J)
   WRITE (NOUT, *)
   WRITE (NOUT, 99999) ' Calculation with TOL =', TOL
   X = 0.0e0
   Y(1) = 0.5e0
   Y(2) = 0.5e0
   Y(3) = PI/5.0e0
   K = 4
```

D02CJF.6 [NP3546/20A]

```
H = (XEND-X)/real(K+1)
         WRITE (NOUT,*)'
                             Χ
                                       Y(1) Y(2) Y(3)'
         IFAIL = 0
         CALL D02CJF(X,XEND,N,Y,FCN,TOL,'Default',OUT,G,W,IFAIL)
         WRITE (NOUT,99998) ' Root of Y(1) = 0.0 at', X
         WRITE (NOUT, 99997) ' Solution is', (Y(I), I=1, N)
   20 CONTINUE
     WRITE (NOUT, *)
     WRITE (NOUT, *)
     WRITE (NOUT,*) 'Case 2: no intermediate output, root-finding'
      DO 40 J = 4, 5
         TOL = 10.0e0**(-J)
         WRITE (NOUT, *)
         WRITE (NOUT, 99999) ' Calculation with TOL =', TOL
         X = 0.0e0
         Y(1) = 0.5e0
         Y(2) = 0.5e0
         Y(3) = PI/5.0e0
         IFAIL = 0
         CALL D02CJF(X,XEND,N,Y,FCN,TOL,'Default',D02CJX,G,W,IFAIL)
         WRITE (NOUT, 99998) ' Root of Y(1) = 0.0 at', X
         WRITE (NOUT, 99997) 'Solution is', (Y(I), I=1, N)
   40 CONTINUE
     WRITE (NOUT, *)
     WRITE (NOUT, *)
     WRITE (NOUT, *)
                     'Case 3: intermediate output, no root-finding'
      DO 60 J = 4, 5
         TOL = 10.0e0 * * (-J)
         WRITE (NOUT, *)
         WRITE (NOUT, 99999) ' Calculation with TOL =', TOL
         X = 0.0e0
         Y(1) = 0.5e0
         Y(2) = 0.5e0
         Y(3) = PI/5.0e0
         K = 4
         H = (XEND-X)/real(K+1)
         WRITE (NOUT,*) '
                                         Y(1)
                                                      Y(2)
                                                                   Y(3)'
                             X
         IFAIL = 0
*
         CALL DO2CJF(X, XEND, N, Y, FCN, TOL, 'Default', OUT, DO2CJW, W, IFAIL)
   60 CONTINUE
     WRITE (NOUT, *)
     WRITE (NOUT, *)
     WRITE (NOUT, *)
     +'Case 4: no intermediate output, no root-finding ( integrate to XE
     +ND) '
     DO 80 J = 4, 5
         TOL = 10.0e0**(-J)
         WRITE (NOUT, *)
         WRITE (NOUT, 99999) ' Calculation with TOL =', TOL
         X = 0.0e0
         Y(1) = 0.5e0
         Y(2) = 0.5e0
         Y(3) = PI/5.0e0
         WRITE (NOUT,*) '
                                         Y(1)
                                                      Y(2)
                                                                  Y(3)'
         WRITE (NOUT, 99996) X, (Y(I), I=1, N)
         IFAIL = 0
         CALL DO2CJF(X, XEND, N, Y, FCN, TOL, 'Default', DO2CJX, DO2CJW, W, IFAIL)
         WRITE (NOUT, 99996) X, (Y(I), I=1, N)
   80 CONTINUE
     STOP
99999 FORMAT (1X,A,e8.1)
99998 FORMAT (1X,A,F7.3)
```

```
99997 FORMAT (1X,A,3F13.5)
99996 FORMAT (1X,F8.2,3F13.5)
     END
     SUBROUTINE OUT(X,Y)
     .. Parameters ..
                NOUT
     INTEGER
     PARAMETER
                   (NOUT=6)
     INTEGER N
PARAMETER (N=3)
     .. Scalar Arguments ..
     real
           X
     .. Array Arguments ..
     real
             Y(N)
     .. Scalars in Common ..
             H, XEND
     real
     INTEGER
                   Ι
     .. Local Scalars ..
     INTEGER J
     .. Intrinsic Functions ..
     INTRINSIC real
     .. Common blocks ..
     COMMON XEND, H, I
     .. Executable Statements ..
     WRITE (NOUT, 99999) X, (Y(J), J=1, N)
     X = XEND - real(I) *H
     I = I - 1
     RETURN
99999 FORMAT (1X,F8.2,3F13.5)
     END
     SUBROUTINE FCN(T,Y,F)
     .. Parameters ..
     INTEGER
     INTEGER N
PARAMETER (N=3)
     .. Scalar Arguments ..
     real
           T
     .. Array Arguments ..
            F(N), Y(N)
     real
     .. Intrinsic Functions ..
     INTRINSIC COS, TAN
     .. Executable Statements ..
     F(1) = TAN(Y(3))
     F(2) = -0.032e0*TAN(Y(3))/Y(2) - 0.02e0*Y(2)/COS(Y(3))
     F(3) = -0.032e0/Y(2)**2
     RETURN
     END
     real FUNCTION G(T,Y)
     .. Parameters ..
     INTEGER N
PARAMETER (N=3)
     .. Scalar Arguments ..
     real T
     .. Array Arguments ..
                   Y(N)
     .. Executable Statements ..
     G = Y(1)
     RETURN
     END
```

9.2 Program Data

None.

9.3 Program Results

D02CJF Example Program Results

D02CJF.8 [NP3546/20A]

```
Case 1: intermediate output, root-finding
 Calculation with TOL = 0.1E-03
    X Y(1) Y(2)
0.00 0.50000 0.50000
                                            Y(3)
                                          0.62832
    0.00
              1.54931 0.40548
                                          0.30662
    2.00
          1.74229 0.37433 -0.12890
1.00554 0.41731 -0.55068
    4.00
    6.00
  Root of Y(1) = 0.0 at 7.288
  Solution is
                  -0.00000 0.47486 -0.76011
 Calculation with TOL = 0.1E-04
         Y(1)
                                       r(3)
0.62832
              Y(1) Y(2)
0.50000 0.50000
                              Y(2)
    0.00
              1.54933 0.40548
    2.00
    4.001.742320.374336.001.005520.41731
                                           -0.12891
                                           -0.55069
  Root of Y(1) = 0.0 at 7.288
  Solution is -0.00000 0.47486 -0.76010
Case 2: no intermediate output, root-finding
 Calculation with TOL = 0.1E-03
 Root of Y(1) = 0.0 at 7.288
  Solution is -0.00000
                                0.47486 -0.76011
 Calculation with TOL = 0.1E-04
  Root of Y(1) = 0.0 at 7.288
  Solution is -0.00000
                               0.47486
                                            -0.76010
Case 3: intermediate output, no root-finding
  Y(1) Y(2) Y(3)

0.00 0.50000 0.50000 0.62832
2.00 1.54931 0.40548 0.30662
4.00 1.74229 0.37433 -0.12890
6.00 1.00554 0.41731 -0.55068
8.00 -0.74589 0.51299 -0.85371
10.00 -3.62813 0.63325
 Calculation with TOL = 0.1E-03
 Calculation with TOL = 0.1E-04
           Y(1)
             Y(1) Y(2) Y(3)

0.50000 0.50000 0.62832

1.54933 0.40548 0.30662

1.74232 0.37433 -0.12891
                             Y(2)
                                            Y(3)
    X
    0.00
    2.00
```

Case 4: no intermediate output, no root-finding (integrate to XEND)

-0.55069

-0.85372

-1.05153

0.37433 0.41731

0.51299

0.63326

Calculation with TOL = 0.1E-03 X Y(1) Y(2) Y(3) 0.50000 0.62832 0.00 0.50000 -1.05152 0.63325 10.00 **-**3.62813 Calculation with TOL = 0.1E-04 X Y(1) Y(2) Y(3) 0.00 0.50000 0.50000 0.62832 10.00 -3.62829 0.63326 -1.05153

1.74232 1.00552

-0.74601

-3.62829

4.00 6.00

8.00

10.00

[NP3546/20A] D02CJF.9 (last)