

NAG Fortran Library Routine Document

E02BBF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

E02BBF evaluates a cubic spline from its B-spline representation.

2 Specification

```
SUBROUTINE E02BBF(NCAP7, LAMDA, C, X, S, IFAIL)
INTEGER          NCAP7, IFAIL
real            LAMDA(NCAP7), C(NCAP7), X, S
```

3 Description

This routine evaluates the cubic spline $s(x)$ at a prescribed argument x from its augmented knot set λ_i , for $i = 1, 2, \dots, n + 7$, (see E02BAF) and from the coefficients c_i , for $i = 1, 2, \dots, q$ in its B-spline representation

$$s(x) = \sum_{i=1}^q c_i N_i(x).$$

Here $q = \bar{n} + 3$, where \bar{n} is the number of intervals of the spline, and $N_i(x)$ denotes the normalised B-spline of degree 3 defined upon the knots $\lambda_i, \lambda_{i+1}, \dots, \lambda_{i+4}$. The prescribed argument x must satisfy $\lambda_4 \leq x \leq \lambda_{\bar{n}+4}$.

It is assumed that $\lambda_j \geq \lambda_{j-1}$, for $j = 2, 3, \dots, \bar{n} + 7$, and $\lambda_{\bar{n}+4} > \lambda_4$.

If x is a point at which 4 knots coincide, $s(x)$ is discontinuous at x ; in this case, S contains the value defined as x is approached from the right.

The method employed is that of evaluation by taking convex combinations due to de Boor (1972). For further details of the algorithm and its use see Cox (1972a) and Cox and Hayes (1973).

It is expected that a common use of E02BBF will be the evaluation of the cubic spline approximations produced by E02BAF. A generalization of E02BBF which also forms the derivative of $s(x)$ is E02BCF. E02BCF takes about 50% longer than E02BBF.

4 References

Cox M G (1972a) The numerical evaluation of B-splines *J. Inst. Math. Appl.* **10** 134–149

Cox M G (1978) The numerical evaluation of a spline from its B-spline representation *J. Inst. Math. Appl.* **21** 135–143

Cox M G and Hayes J G (1973) Curve fitting: a guide and suite of algorithms for the non-specialist user *NPL Report NAC26* National Physical Laboratory

de Boor C (1972) On calculating with B-splines *J. Approx. Theory* **6** 50–62

5 Parameters

- 1: NCAP7 – INTEGER *Input*
On entry: $\bar{n} + 7$, where \bar{n} is the number of intervals (one greater than the number of interior knots, i.e., the knots strictly within the range λ_4 to $\lambda_{\bar{n}+4}$) over which the spline is defined.
Constraint: $\text{NCAP7} \geq 8$.

- 2: LAMDA(NCAP7) – *real* array *Input*
On entry: LAMDA(j) must be set to the value of the j th member of the complete set of knots, λ_j for $j = 1, 2, \dots, \bar{n} + 7$.
Constraint: the LAMDA(j) must be in non-decreasing order with LAMDA(NCAP7 – 3) > LAMDA(4).

- 3: C(NCAP7) – *real* array *Input*
On entry: the coefficient c_i of the B-spline $N_i(x)$, for $i = 1, 2, \dots, \bar{n} + 3$. The remaining elements of the array are not used.

- 4: X – *real* *Input*
On entry: the argument x at which the cubic spline is to be evaluated.
Constraint: $\text{LAMDA}(4) \leq X \leq \text{LAMDA}(\text{NCAP7} - 3)$.

- 5: S – *real* *Output*
On exit: the value of the spline, $s(x)$.

- 6: IFAIL – INTEGER *Input/Output*
On entry: IFAIL must be set to 0, –1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.
On exit: IFAIL = 0 unless the routine detects an error (see Section 6).
 For environments where it might be inappropriate to halt program execution when an error is detected, the value –1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. **When the value –1 or 1 is used it is essential to test the value of IFAIL on exit.**

6 Error Indicators and Warnings

If on entry IFAIL = 0 or –1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

The argument X does not satisfy $\text{LAMDA}(4) \leq X \leq \text{LAMDA}(\text{NCAP7} - 3)$.

In this case the value of S is set arbitrarily to zero.

IFAIL = 2

$\text{NCAP7} < 8$, i.e., the number of interior knots is negative.

7 Accuracy

The computed value of $s(x)$ has negligible error in most practical situations. Specifically, this value has an **absolute** error bounded in modulus by $18 \times c_{\max} \times \text{machine precision}$, where c_{\max} is the largest in modulus of c_j, c_{j+1}, c_{j+2} and c_{j+3} , and j is an integer such that $\lambda_{j+3} \leq x \leq \lambda_{j+4}$. If c_j, c_{j+1}, c_{j+2} and c_{j+3} are all of the same sign, then the computed value of $s(x)$ has a **relative** error not exceeding $20 \times \text{machine precision}$ in modulus. For further details see Cox (1978).

8 Further Comments

The time taken by the routine is approximately $C \times (1 + 0.1 \times \log(\bar{n} + 7))$ seconds, where C is a machine-dependent constant.

Note: the routine does not test all the conditions on the knots given in the description of LAMDA in Section 5, since to do this would result in a computation time approximately linear in $\bar{n} + 7$ instead of $\log(\bar{n} + 7)$. All the conditions are tested in E02BAF, however.

9 Example

Evaluate at 9 equally-spaced points in the interval $1.0 \leq x \leq 9.0$ the cubic spline with (augmented) knots 1.0, 1.0, 1.0, 1.0, 3.0, 6.0, 8.0, 9.0, 9.0, 9.0, 9.0 and normalised cubic B-spline coefficients 1.0, 2.0, 4.0, 7.0, 6.0, 4.0, 3.0.

The example program is written in a general form that will enable a cubic spline with \bar{n} intervals, in its normalised cubic B-spline form, to be evaluated at m equally-spaced points in the interval $\text{LAMDA}(4) \leq x \leq \text{LAMDA}(\bar{n} + 4)$. The program is self-starting in that any number of data sets may be supplied.

9.1 Program Text

Note: the listing of the example program presented below uses **bold italicised** terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
*      E02BBF Example Program Text
*      Mark 14 Revised.  NAG Copyright 1989.
*      .. Parameters ..
      INTEGER          NC7MAX
      PARAMETER        (NC7MAX=200)
      INTEGER          NIN, NOUT
      PARAMETER        (NIN=5,NOUT=6)
*      .. Local Scalars ..
      real             A, B, S, X
      INTEGER          IFAIL, J, M, NCAP, R
*      .. Local Arrays ..
      real             C(NC7MAX), LAMDA(NC7MAX)
*      .. External Subroutines ..
      EXTERNAL         E02BBF
*      .. Intrinsic Functions ..
      INTRINSIC        real
*      .. Executable Statements ..
      WRITE (NOUT,*) 'E02BBF Example Program Results'
*      Skip heading in data file
      READ (NIN,*)
20 READ (NIN,*,END=80) M
      IF (M.GT.0) THEN
        READ (NIN,*) NCAP
        IF (NCAP+7.LE.NC7MAX) THEN
          READ (NIN,*) (LAMDA(J),J=1,NCAP+7)
          READ (NIN,*) (C(J),J=1,NCAP+3)
          A = LAMDA(4)
          B = LAMDA(NCAP+4)
          WRITE (NOUT,*)
          WRITE (NOUT,*)
          +      '      J      LAMDA(J)      B-spline coefficient (J-2)'
          WRITE (NOUT,*)
```

```

      DO 40 J = 1, NCAP + 7
        IF (J.LT.3 .OR. J.GT.NCAP+5) THEN
          WRITE (NOUT,99999) J, LAMDA(J)
        ELSE
          WRITE (NOUT,99999) J, LAMDA(J), C(J-2)
        END IF
40      CONTINUE
      WRITE (NOUT,*)
      WRITE (NOUT,*)
      +      ' R      Argument      Value of cubic spline'
      WRITE (NOUT,*)
      DO 60 R = 1, M
        X = (real(M-R)*A+real(R-1)*B)/real(M-1)
        IFAIL = 0
*
        CALL E02BBF(NCAP+7,LAMDA,C,X,S,IFAIL)
*
        WRITE (NOUT,99999) R, X, S
60      CONTINUE
      GO TO 20
    END IF
  END IF
80 STOP
*
99999 FORMAT (1X,I3,F14.4,F21.4)
END

```

9.2 Program Data

E02BBF Example Program Data

```

9
4
1.00
1.00
1.00
1.00
3.00
6.00
8.00
9.00
9.00
9.00
9.00
1.00
2.00
4.00
7.00
6.00
4.00
3.00

```

9.3 Program Results

E02BBF Example Program Results

J	LAMDA(J)	B-spline coefficient (J-2)
1	1.0000	
2	1.0000	
3	1.0000	1.0000
4	1.0000	2.0000
5	3.0000	4.0000
6	6.0000	7.0000
7	8.0000	6.0000
8	9.0000	4.0000
9	9.0000	3.0000
10	9.0000	
11	9.0000	

R	Argument	Value of cubic spline
---	----------	-----------------------

1	1.0000	1.0000
2	2.0000	2.3779
3	3.0000	3.6229
4	4.0000	4.8327
5	5.0000	5.8273
6	6.0000	6.3571
7	7.0000	6.1905
8	8.0000	5.1667
9	9.0000	3.0000
