

NAG Fortran Library Routine Document

E02DEF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

E02DEF calculates values of a bicubic spline from its B-spline representation.

2 Specification

```
SUBROUTINE E02DEF(M, PX, PY, X, Y, LAMDA, MU, C, FF, WRK, IWRK, IFAIL)
  INTEGER          M, PX, PY, IWRK(PY-4), IFAIL
  real            X(M), Y(M), LAMDA(PX), MU(PY), C((PX-4)*(PY-4)),
1                  FF(M), WRK(PY-4)
```

3 Description

This routine calculates values of the bicubic spline $s(x, y)$ at prescribed points (x_r, y_r) , for $r = 1, 2, \dots, m$, from its augmented knot sets $\{\lambda\}$ and $\{\mu\}$ and from the coefficients c_{ij} , for $i = 1, 2, \dots, PX - 4$; $j = 1, 2, \dots, PY - 4$, in its B-spline representation

$$s(x, y) = \sum_{ij} c_{ij} M_i(x) N_j(y).$$

Here $M_i(x)$ and $N_j(y)$ denote normalised cubic B-splines, the former defined on the knots λ_i to λ_{i+4} and the latter on the knots μ_j to μ_{j+4} .

This routine may be used to calculate values of a bicubic spline given in the form produced by E01DAF, E02DAF, E02DCF and E02DDF. It is derived from the routine B2VRE in Anthony *et al.* (1982).

4 References

Anthony G T, Cox M G and Hayes J G (1982) *DASL – Data Approximation Subroutine Library* National Physical Laboratory

Cox M G (1978) The numerical evaluation of a spline from its B-spline representation *J. Inst. Math. Appl.* **21** 135–143

5 Parameters

1: M – INTEGER *Input*

On entry: m , the number of points at which values of the spline are required.

Constraint: $M \geq 1$.

2: PX – INTEGER *Input*

3: PY – INTEGER *Input*

On entry: PX and PY must specify the total number of knots associated with the variables x and y respectively. They are such that $PX - 8$ and $PY - 8$ are the corresponding numbers of interior knots.

Constraint: $PX \geq 8$ and $PY \geq 8$.

- 4: X(M) – *real* array Input
 5: Y(M) – *real* array Input

On entry: X and Y must contain x_r and y_r , for $r = 1, 2, \dots, m$, respectively. These are the co-ordinates of the points at which values of the spline are required. The order of the points is immaterial.

Constraint: X and Y must satisfy

$$\text{LAMDA}(4) \leq X(r) \leq \text{LAMDA}(\text{PX} - 3)$$

and

$$\text{MU}(4) \leq Y(r) \leq \text{MU}(\text{PY} - 3), \quad r = 1, 2, \dots, m.$$

The spline representation is not valid outside these intervals..

- 6: LAMDA(PX) – *real* array Input
 7: MU(PY) – *real* array Input

On entry: LAMDA and MU must contain the complete sets of knots $\{\lambda\}$ and $\{\mu\}$ associated with the x and y variables respectively.

Constraint: the knots in each set must be in non-decreasing order, with $\text{LAMDA}(\text{PX} - 3) > \text{LAMDA}(4)$ and $\text{MU}(\text{PY} - 3) > \text{MU}(4)$.

- 8: C((PX-4)*(PY-4)) – *real* array Input

On entry: C((PY - 4) $\times$ (i - 1) + j) must contain the coefficient c_{ij} described in Section 3, for $i = 1, 2, \dots, \text{PX} - 4$; $j = 1, 2, \dots, \text{PY} - 4$.

- 9: FF(M) – *real* array Output

On exit: FF(r) contains the value of the spline at the point (x_r, y_r) , for $r = 1, 2, \dots, m$.

- 10: WRK(PY-4) – *real* array Workspace
 11: IWRK(PY-4) – INTEGER array Workspace

- 12: IFAIL – INTEGER Input/Output

On entry: IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.

On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

On entry, M < 1,
 or PY < 8,
 or PX < 8.

IFAIL = 2

On entry, the knots in array LAMDA, or those in array MU, are not in non-decreasing order, or $\text{LAMDA}(\text{PX} - 3) \leq \text{LAMDA}(4)$, or $\text{MU}(\text{PY} - 3) \leq \text{MU}(4)$.

IFAIL = 3

On entry, at least one of the prescribed points (x_r, y_r) lies outside the rectangle defined by $\text{LAMDA}(4)$, $\text{LAMDA}(\text{PX} - 3)$ and $\text{MU}(4)$, $\text{MU}(\text{PY} - 3)$.

7 Accuracy

The method used to evaluate the B-splines is numerically stable, in the sense that each computed value of $s(x_r, y_r)$ can be regarded as the value that would have been obtained in exact arithmetic from slightly perturbed B-spline coefficients. See Cox (1978) for details.

8 Further Comments

Computation time is approximately proportional to the number of points, m , at which the evaluation is required.

9 Example

This program reads in knot sets $\text{LAMDA}(1), \dots, \text{LAMDA}(\text{PX})$ and $\text{MU}(1), \dots, \text{MU}(\text{PY})$, and a set of bicubic spline coefficients c_{ij} . Following these are a value for m and the co-ordinates (x_r, y_r) , for $r = 1, 2, \dots, m$, at which the spline is to be evaluated.

9.1 Program Text

Note: the listing of the example program presented below uses *bold italicised* terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
*      E02DEF Example Program Text
*      Mark 14 Release.  NAG Copyright 1989.
*      .. Parameters ..
      INTEGER                NIN, NOUT
      PARAMETER              (NIN=5,NOUT=6)
      INTEGER                MMAX, PXMAX, PYMAX
      PARAMETER              (MMAX=20,PXMAX=MMAX,PYMAX=PXMAX)
*      .. Local Scalars ..
      INTEGER                I, IFAIL, M, PX, PY
*      .. Local Arrays ..
      real                   C((PXMAX-4)*(PYMAX-4)), FF(MMAX), LAMDA(PXMAX),
+      MU(PYMAX), WRK(PYMAX-7), X(MMAX), Y(MMAX)
      INTEGER                IWRK(PYMAX-7)
*      .. External Subroutines ..
      EXTERNAL               E02DEF
*      .. Executable Statements ..
      WRITE (NOUT,*) 'E02DEF Example Program Results'
*      Skip heading in data file
      READ (NIN,*)
*      Read PX and PY, the number of knots in the X and Y directions.
      READ (NIN,*) PX, PY
      IF (PX.LE.PXMAX .AND. PY.LE.PYMAX) THEN
*      Read the knots LAMDA(1) .. LAMDA(PX) and MU(1) .. MU(PY).
      READ (NIN,*) (LAMDA(I),I=1,PX)
      READ (NIN,*) (MU(I),I=1,PY)
*      Read C, the bicubic spline coefficients.
      READ (NIN,*) (C(I),I=1,(PX-4)*(PY-4))
*      Read M, the number of spline evaluation points.
      READ (NIN,*) M
      IF (M.LE.MMAX) THEN
*      Read the X and Y co-ordinates of the evaluation points.
      DO 20 I = 1, M
```

```

      READ (NIN,*) X(I), Y(I)
20    CONTINUE
      IFAIL = 0
*
*      Evaluate the spline at the M points.
      CALL E02DEF(M,PX,PY,X,Y,LAMDA,MU,C,FF,WRK,IWRK,IFAIL)
*
*      Print the results.
      WRITE (NOUT,*)
      WRITE (NOUT,*) '      I      X(I)      Y(I)      FF(I) '
      WRITE (NOUT,99999) (I,X(I),Y(I),FF(I),I=1,M)
      END IF
    END IF
  STOP
*
99999 FORMAT (1X,I7,3F11.3)
END

```

9.2 Program Data

E02DEF Example Program Data

11	10										PX	PY
1.0	1.0	1.0	1.0	1.3	1.5	1.6	2.0	2.0	2.0	2.0	LAMDA(1) .. LAMDA(PX)	
0.0	0.0	0.0	0.0	0.4	0.7	1.0	1.0	1.0	1.0	1.0	MU(1) .. MU(PY)	
1.0000		1.1333		1.3667		1.7000		1.9000		2.0000		
1.2000		1.3333		1.5667		1.9000		2.1000		2.2000		
1.5833		1.7167		1.9500		2.2833		2.4833		2.5833		
2.1433		2.2767		2.5100		2.8433		3.0433		3.1433		
2.8667		3.0000		3.2333		3.5667		3.7667		3.8667		
3.4667		3.6000		3.8333		4.1667		4.3667		4.4667		
4.0000		4.1333		4.3667		4.7000		4.9000		5.0000		
7											Spline coefficients, C	
1.0	0.0										M	
1.1	0.1										X(1), Y(1)	
1.5	0.7											
1.6	0.4											
1.9	0.3											
1.9	0.8											
2.0	1.0										X(M), Y(M)	

9.3 Program Results

E02DEF Example Program Results

I	X(I)	Y(I)	FF(I)
1	1.000	0.000	1.000
2	1.100	0.100	1.310
3	1.500	0.700	2.950
4	1.600	0.400	2.960
5	1.900	0.300	3.910
6	1.900	0.800	4.410
7	2.000	1.000	5.000
