NAG Fortran Library Routine Document

F04BCF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F04BCF computes the solution to a real system of linear equations AX = B, where A is an n by n tridiagonal matrix and X and B are n by r matrices. An estimate of the condition number of A and an error bound for the computed solution are also returned.

2 Specification

SUBROUTINE F04BCF 1	(N, NRHS, DL, D, DU, DU2, IPIV, B, LDB, RCOND, ERRBND, IFAIL)
INTEGER	N, NRHS, IPIV(*), LDB, IFAIL
<i>double precision</i>	DL(*), D(*), DU(*), DU2(*), B(LDB,*), RCOND, ERRBND

3 Description

The LU decomposition with partial pivoting and row interchanges is used to factor A as A = PLU, where P is a permutation matrix, L is unit lower triangular with at most one non-zero sub-diagonal element, and U is an upper triangular band matrix with two super-diagonals. The factored form of A is then used to solve the system of equations AX = B.

Note that the equations $A^T X = B$ may be solved by interchanging the order of the arguments DU and DL.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia URL: http://www.netlib.org/lapack/lug

Higham N J (2002) Accuracy and Stability of Numerical Algorithms (2nd Edition) SIAM, Philadelphia

5 Parameters

1: N – INTEGER

On entry: the number of linear equations n, i.e., the order of the matrix A. Constraint: $N \ge 0$.

2: NRHS – INTEGER

On entry: the number of right-hand sides r, i.e., the number of columns of the matrix B. Constraint: NRHS ≥ 0 .

3: DL(*) – *double precision* array

Note: the dimension of the array DL must be at least max(1, N - 1).

On entry: DL must contain the (n-1) sub-diagonal elements of the matrix A.

On exit: if IFAIL ≥ 0 , DL is overwritten by the (n-1) multipliers that define the matrix L from the LU factorization of A.

Input

Input

Input/Output

4: D(*) - double precision array Input/Output Note: the dimension of the array D must be at least max(1, N).

On entry: D must contain the n diagonal elements of the matrix A.

On exit: if IFAIL ≥ 0 , D is overwritten by the n diagonal elements of the upper triangular matrix U from the LU factorization of A.

5: DU(*) – *double precision* array

Note: the dimension of the array DU must be at least max(1, N - 1).

On entry: DU must contain the (n-1) super-diagonal elements of the matrix A

On exit: if IFAIL ≥ 0 , DU is overwritten by the (n-1) elements of the first super-diagonal of U.

6: DU2(*) - double precision array

Note: the dimension of the array DU2 must be at least max(1, N - 2).

On exit: if IFAIL ≥ 0 , DU2 returns the (n-2) elements of the second super-diagonal of U.

7: IPIV(*) - INTEGER array

Note: the dimension of the array IPIV must be at least max(1, N).

On exit: if IFAIL ≥ 0 , the pivot indices that define the permutation matrix P; at the *i*th step row *i* of the matrix was interchanged with row IPIV(*i*). IPIV(*i*) will always be either *i* or (*i* + 1); IPIV(*i*) = *i* indicates a row interchange was not required.

8: B(LDB,*) – *double precision* array

Note: the second dimension of the array B must be at least max(1, NRHS). To solve the equations Ax = b, where b is a single right-hand side, B may be supplied as a one-dimensional array with length LDB = max(1, N).

On entry: the n by r matrix of right-hand sides B.

On exit: if IFAIL = 0 or N + 1, the n by r solution matrix X.

9: LDB – INTEGER

On entry: the first dimension of the array B as declared in the (sub)program from which F04BCF is called.

Constraint: LDB $\geq \max(1, N)$.

10: RCOND – *double precision*

On exit: if IFAIL ≥ 0 , an estimate of the reciprocal of the condition number of the matrix A, computed as $\text{RCOND} = 1/(||A||_1 ||A^{-1}||_1)$.

11: ERRBND – *double precision*

On exit: if IFAIL = 0 or N + 1, an estimate of the forward error bound for a computed solution \hat{x} , such that $\|\hat{x} - x\|_1 / \|x\|_1 \le \text{ERRBND}$, where \hat{x} is a column of the computed solution returned in the array B and x is the corresponding column of the exact solution X. If RCOND is less than *machine precision*, then ERRBND is returned as unity.

12: IFAIL – INTEGER

On entry: IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.

On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

Input/Output

Input/Output

Output

Output

Output

Output

Input/Output

Input

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL < 0 and IFAIL $\neq -999$

If IFAIL = -i, the *i*th argument had an illegal value.

 $\mathrm{IFAIL} = -999$

Allocation of memory failed. The INTEGER allocatable memory required is N, and the *double precision* allocatable memory required is $2 \times N$. In this case the factorization and the solution X have been computed, but RCOND and ERRBND have not been computed.

 $\mathrm{IFAIL} > 0$ and $\mathrm{IFAIL} \leq N$

If IFAIL = i, u_{ii} is exactly zero. The factorization has been completed, but the factor U is exactly singular, so the solution could not be computed.

IFAIL = N + 1

RCOND is less than *machine precision*, so that the matrix A is numerically singular. A solution to the equations AX = B has nevertheless been computed.

7 Accuracy

The computed solution for a single right-hand side, \hat{x} , satisfies an equation of the form

$$(A+E)\hat{x} = b,$$

where

$$||E||_1 = O(\epsilon) ||A||_1$$

and ϵ is the *machine precision*. An approximate error bound for the computed solution is given by

$$\frac{\|\hat{x} - x\|_1}{\|x\|_1} \le \kappa(A) \frac{\|E\|_1}{\|A\|_1},$$

where $\kappa(A) = ||A^{-1}||_1 ||A||_1$, the condition number of A with respect to the solution of the linear equations. F04BCF uses the approximation $||E||_1 = \epsilon ||A||_1$ to estimate ERRBND. See Section 4.4 of Anderson *et al.* (1999) for further details.

8 Further Comments

The total number of floating-point operations required to solve the equations AX = B is proportional to nr. The condition number estimation typically requires between four and five solves and never more than eleven solves, following the factorization.

In practice the condition number estimator is very reliable, but it can underestimate the true condition number; see Section 15.3 of Higham (2002) for further details.

The complex analogue of F04BCF is F04CCF.

9 Example

To solve the equations

$$AX = B,$$

where A is the tridiagonal matrix

$$A = \begin{pmatrix} 3.0 & 2.1 & 0 & 0 & 0 \\ 3.4 & 2.3 & -1.0 & 0 & 0 \\ 0 & 3.6 & -5.0 & 1.9 & 0 \\ 0 & 0 & 7.0 & -0.9 & 8.0 \\ 0 & 0 & 0 & -6.0 & 7.1 \end{pmatrix}$$

and

$$B = \begin{pmatrix} 2.7 & 6.6\\ -0.5 & 10.8\\ 2.6 & -3.2\\ 0.6 & -11.2\\ 2.7 & 19.1 \end{pmatrix}.$$

An estimate of the condition number of A and an approximate error bound for the computed solutions are also printed.

9.1 Program Text

Note: the listing of the example program presented below uses *bold italicised* terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
FO4BCF Example Program Text
*
     Mark 21 Release. NAG Copyright 2004.
*
*
      .. Parameters ..
      INTEGER
                       NIN, NOUT
                        (NIN=5,NOUT=6)
     PARAMETER
      INTEGER
                       NMAX, NRHSMX
     PARAMETER
                       (NMAX=8,NRHSMX=2)
     INTEGER
                       LDB
     PARAMETER
                        (LDB=NMAX)
      .. Local Scalars ..
     DOUBLE PRECISION ERRBND, RCOND
      INTEGER
                       I, IERR, IFAIL, J, N, NRHS
      .. Local Arrays ..
*
     DOUBLE PRECISION B(LDB,NRHSMX), D(NMAX), DL(NMAX-1), DU(NMAX-1),
     +
                       DU2(NMAX-2)
      INTEGER
                       IPIV(NMAX)
      .. External Subroutines ..
EXTERNAL F04BCF, X04CAF
4
      EXTERNAL
      .. Executable Statements ..
      WRITE (NOUT, *) 'FO4BCF Example Program Results'
      WRITE (NOUT, *)
      Skip heading in data file
     READ (NIN,*)
     READ (NIN, *) N, NRHS
      IF (N.LE.NMAX .AND. NRHS.LE.NRHSMX) THEN
*
         Read A and B from data file
         READ (NIN,*) (DU(I),I=1,N-1)
         READ (NIN,*) (D(I),I=1,N)
         READ (NIN, \star) (DL(I), I=1, N-1)
         READ (NIN,*) ((B(I,J),J=1,NRHS),I=1,N)
         Solve the equations AX = B for X
*
         IFAIL = -1
         CALL F04BCF(N,NRHS,DL,D,DU,DU2,IPIV,B,LDB,RCOND,ERRBND,IFAIL)
*
```

F04BCF

```
IF (IFAIL.EQ.O) THEN
*
*
            Print solution, estimate of condition number and approximate
*
            error bound
*
            IERR = 0
            CALL X04CAF('General',' ',N,NRHS,B,LDB,'Solution',IERR)
*
            WRITE (NOUT, *)
            WRITE (NOUT, *) 'Estimate of condition number'
            WRITE (NOUT, 99999) 1.0D0/RCOND
            WRITE (NOUT, *)
            WRITE (NOUT, *)
              'Estimate of error bound for computed solutions'
     +
            WRITE (NOUT, 99999) ERRBND
         ELSE IF (IFAIL.EQ.N+1) THEN
*
            Matrix A is numerically singular. Print estimate of
*
            reciprocal of condition number and solution
*
*
            WRITE (NOUT, *)
            WRITE (NOUT, *) 'Estimate of reciprocal of condition number'
            WRITE (NOUT, 99999) RCOND
            WRITE (NOUT, *)
            IERR = 0
            CALL X04CAF('General',' ',N,NRHS,B,LDB,'Solution',IERR)
*
         ELSE IF (IFAIL.GT.O .AND. IFAIL.LE.N) THEN
*
*
            The upper triangular matrix U is exactly singular. Print
            details of factorization
*
            WRITE (NOUT, *) 'Details of factorization'
            WRITE (NOUT, *)
            WRITE (NOUT, *) ' Second super-diagonal of U'
            WRITE (NOUT, 99998) (DU2(I), I=1, N-2)
            WRITE (NOUT, *)
            WRITE (NOUT,*) ' First super-diagonal of U'
            WRITE (NOUT, 99998) (DU(I), I=1, N-1)
            WRITE (NOUT, *)
            WRITE (NOUT, *) ' Main diagonal of U'
            WRITE (NOUT, 99998) (D(I), I=1, N)
            WRITE (NOUT, *)
            WRITE (NOUT, *) ' Multipliers'
            WRITE (NOUT, 99998) (DL(I), I=1, N-1)
            WRITE (NOUT, *)
            WRITE (NOUT, *) ' Vector of interchanges'
            WRITE (NOUT, 99997) (IPIV(I), I=1, N)
         END IF
      ELSE
         WRITE (NOUT, *) 'NMAX and/or NRHSMX too small'
      END IF
      STOP
99999 FORMAT (6X,1P,E9.1)
99998 FORMAT (1X,8F9.4)
99997 FORMAT (1X,819)
     END
```

9.2 Program Data

F04BCF Example Program Data

 5
 2
 :Values of N and NRHS

 2.1
 -1.0
 1.9
 8.0
 :End of superdiagonal DU

 3.0
 2.3
 -5.0
 -0.9
 7.1
 :End of diagonal D

 3.4
 3.6
 7.0
 -6.0
 :End of subdiagonal DL

 2.7
 6.6
 -0.5
 10.8
 .6
 -3.2

 0.6
 -11.2
 .7
 19.1
 :End of matrix B

9.3 Program Results

FO4BCF Example Program Results

Solution

1 2 5.0000 -4.0000 -3.0000 -4.0000 1 7.0000 2 3 -2.0000 4 -4.0000 5 -3.0000 1.0000 Estimate of condition number 9.3E+01 Estimate of error bound for computed solutions 1.0E-14