NAG Fortran Library Routine Document F04D.JF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

1 Purpose

F04DJF computes the solution to a complex system of linear equations AX = B, where A is an n by n complex symmetric matrix, stored in packed format and X and B are n by r matrices. An estimate of the condition number of A and an error bound for the computed solution are also returned.

2 Specification

```
SUBROUTINE F04DJF (UPLO, N, NRHS, AP, IPIV, B, LDB, RCOND, ERRBND, IFAIL)

INTEGER

N, NRHS, IPIV(*), LDB, IFAIL

double precision

complex*16

CHARACTER*1

CPLO N, NRHS, AP, IPIV, B, LDB, RCOND, ERRBND, IFAIL

RCOND, ERRBND

AP(*), B(LDB,*)
```

3 Description

The diagonal pivoting method is used to factor A as $A = UDU^T$, if UPLO = 'U', or $A = LDL^T$, if UPLO = 'L', where U (or L) is a product of permutation and unit upper (lower) triangular matrices, and D is symmetric and block diagonal with 1 by 1 and 2 by 2 diagonal blocks. The factored form of A is then used to solve the system of equations AX = B.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia URL: http://www.netlib.org/lapack/lug

Higham N J (2002) Accuracy and Stability of Numerical Algorithms (2nd Edition) SIAM, Philadelphia

5 Parameters

1: UPLO – CHARACTER*1

Input

On entry: if UPLO = 'U', the upper triangle of the matrix A is stored, if UPLO = 'L', the lower triangle of the matrix A is stored.

Constraint: UPLO = 'U' or 'L'.

2: N – INTEGER Input

On entry: the number of linear equations n, i.e., the order of the matrix A.

Constraint: $N \geq 0$.

3: NRHS – INTEGER

Input

On entry: the number of right-hand sides r, i.e., the number of columns of the matrix B.

Constraint: NRHS ≥ 0 .

[NP3657/21] F04DJF.1

4: AP(*) - complex*16 array

Input/Output

Note: the dimension of the array AP must be at least $max(1, N \times (N+1)/2)$.

On entry: the n by n symmetric matrix A, packed columnwise in a linear array. The jth column of the matrix A is stored in the array AP as follows:

if UPLO = 'U',
$$AP(i + (j-1)j/2) = a_{ij}$$
 for $1 \le i \le j$; if UPLO = 'L', $AP(i + (j-1)(2n-j)/2) = a_{ij}$ for $j \le i \le n$.

See Section 8 below for further details.

On exit: if IFAIL ≥ 0 , the block diagonal matrix D and the multipliers used to obtain the factor U or L from the factorization $A = UDU^T$ or $A = LDL^T$ as computed by F07QRF (ZSPTRF), stored as a packed triangular matrix in the same storage format as A.

5: IPIV(*) – INTEGER array

Output

Note: the dimension of the array IPIV must be at least max(1, N).

On exit: if IFAIL ≥ 0 , details of the interchanges and the block structure of D, as determined by F07QRF (ZSPTRF).

If IPIV(k) > 0, then rows and columns k and IPIV(k) were interchanged, and d_{kk} is a 1 by 1 diagonal block;

if UPLO = 'U' and IPIV(k) = IPIV(k-1) < 0, then rows and columns k-1 and -IPIV(k) were interchanged and $d_{k-1:k,k-1:k}$ is a 2 by 2 diagonal block;

if UPLO = 'L' and IPIV(k) = IPIV(k+1) < 0, then rows and columns k+1 and -IPIV(k) were interchanged and $d_{k:k+1,k:k+1}$ is a 2 by 2 diagonal block.

6: B(LDB,*) - complex*16 array

Input/Output

Note: the second dimension of the array B must be at least max(1, NRHS). To solve the equations Ax = b, where b is a single right-hand side, B may be supplied as a one-dimensional array with length LDB = max(1, N).

On entry: the n by r matrix of right-hand sides B.

On exit: if IFAIL = 0 or N + 1, the n by r solution matrix X.

7: LDB – INTEGER

Input

On entry: the first dimension of the array B as declared in the (sub)program from which F04DJF is called.

Constraint: LDB $\geq \max(1, N)$.

8: RCOND – double precision

Output

On exit: if IFAIL ≥ 0 , an estimate of the reciprocal of the condition number of the matrix A, computed as $\text{RCOND} = 1/(\|A\|_1 \|A^{-1}\|_1)$.

9: ERRBND – *double precision*

Output

On exit: if IFAIL = 0 or N + 1, an estimate of the forward error bound for a computed solution \hat{x} , such that $\|\hat{x} - x\|_1 / \|x\|_1 \le \text{ERRBND}$, where \hat{x} is a column of the computed solution returned in the array B and x is the corresponding column of the exact solution X. If RCOND is less than **machine precision**, then ERRBND is returned as unity.

10: IFAIL – INTEGER

Input/Output

On entry: IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.

On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

F04DJF.2 [NP3657/21]

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL < 0 and IFAIL $\neq -999$

If IFAIL = -i, the *i*th argument had an illegal value.

IFAIL = -999

Allocation of memory failed. The *double precision* allocatable memory required is N, and the *complex*16* allocatable memory required is $2 \times N$. Allocation failed before the solution could be computed.

IFAIL > 0 and IFAIL $\le N$

If IFAIL = i, d_{ii} is exactly zero. The factorization has been completed, but the block diagonal matrix D is exactly singular, so the solution could not be computed.

IFAIL = N + 1

RCOND is less than *machine precision*, so that the matrix A is numerically singular. A solution to the equations AX = B has nevertheless been computed.

7 Accuracy

The computed solution for a single right-hand side, \hat{x} , satisfies an equation of the form

$$(A+E)\hat{x}=b$$
,

where

$$||E||_1 = O(\epsilon)||A||_1$$

and ϵ is the *machine precision*. An approximate error bound for the computed solution is given by

$$\frac{\|\hat{x} - x\|_1}{\|x\|_1} \le \kappa(A) \frac{\|E\|_1}{\|A\|_1},$$

where $\kappa(A) = \|A^{-1}\|_1 \|A\|_1$, the condition number of A with respect to the solution of the linear equations. F04DJF uses the approximation $\|E\|_1 = \epsilon \|A\|_1$ to estimate ERRBND. See Section 4.4 of Anderson *et al.* (1999) for further details.

8 Further Comments

The packed storage scheme is illustrated by the following example when n=4 and UPLO = 'U'. Two-dimensional storage of the symmetric matrix A:

$$\begin{array}{ccccc} a_{11} & a_{12} & a_{13} & a_{14} \\ & a_{22} & a_{23} & a_{24} \\ & & a_{33} & a_{34} \\ & & & a_{44} \end{array} \quad \left(a_{ij} = a_{ji}\right)$$

[NP3657/21] F04DJF.3

Packed storage of the upper triangle of A:

The total number of floating-point operations required to solve the equations AX = B is proportional to $(\frac{1}{3}n^3 + 2n^2r)$. The condition number estimation typically requires between four and five solves and never more than eleven solves, following the factorization.

In practice the condition number estimator is very reliable, but it can underestimate the true condition number; see Section 15.3 of Higham (2002) for further details.

Routine F04CJF is for complex Hermitian matrices, and the real analogue of F04DJF is F04BJF.

9 Example

To solve the equations

$$AX = B$$
.

where A is the symmetric indefinite matrix

$$A = \begin{pmatrix} -0.56 + 0.12i & -1.54 - 2.86i & 5.32 - 1.59i & 3.80 + 0.92i \\ -1.54 - 2.86i & -2.83 - 0.03i & -3.52 + 0.58i & -7.86 - 2.96i \\ 5.32 - 1.59i & -3.52 + 0.58i & 8.86 + 1.81i & 5.14 - 0.64i \\ 3.80 + 0.92i & -7.86 - 2.96i & 5.14 - 0.64i & -0.39 - 0.71i \end{pmatrix}$$

and

$$B = \begin{pmatrix} -6.43 + 19.24i & -4.59 - 35.53i \\ -0.49 - 1.47i & 6.95 + 20.49i \\ -48.18 + 66.00i & -12.08 - 27.02i \\ -55.64 + 41.22i & -19.09 - 35.97i \end{pmatrix}.$$

An estimate of the condition number of A, and an approximate error bound for the computed solutions is also printed.

9.1 Program Text

Note: the listing of the example program presented below uses **bold italicised** terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
FO4DJF Example Program Text
      Mark 21 Release. NAG Copyright 2004.
*
      .. Parameters ..
                  NIN, NOUT
      INTEGER
                        (NIN=5, NOUT=6)
      PARAMETER
                       NMAX, NRHSMX
      INTEGER
                        (NMAX=8,NRHSMX=2)
      PARAMETER
      INTEGER
                        (LDB=NMAX)
      PARAMETER
                       UPLO
(UPLO='U')
      CHARACTER
      PARAMETER
      .. Local Scalars ..
      DOUBLE PRECISION ERRBND, RCOND
      INTEGER
                  I, IERR, IFAIL, J, N, NRHS
      .. Local Arrays ..
      COMPLEX *16 AP((NMAX*(NMAX+1))/2), B(LDB,NRHSMX)
INTEGER IPIV(NMAX)
CHARACTER CLABS(1), RLABS(1)
      .. External Subroutines ..
EXTERNAL F04DJF, X04DBF, X04DDF
      .. Executable Statements ..
      WRITE (NOUT, *) 'F04DJF Example Program Results'
      WRITE (NOUT, *)
      Skip heading in data file
      READ (NIN, *)
      READ (NIN, *) N, NRHS
```

F04DJF.4 [NP3657/21]

```
IF (N.LE.NMAX .AND. NRHS.LE.NRHSMX) THEN
   Read the upper or lower triangular part of the matrix A from
   data file
   IF (UPLO.EQ.'U') THEN
     READ (NIN,*) ((AP(I+(J*(J-1))/2),J=I,N),I=1,N)
   ELSE IF (UPLO.EQ.'L') THEN
     READ (NIN, *) ((AP(I+((2*N-J)*(J-1))/2), J=1, I), I=1, N)
  END IF
  Read B from data file
  READ (NIN,*) ((B(I,J),J=1,NRHS),I=1,N)
  Solve the equations AX = B for X
  TFATT = -1
  CALL FO4DJF(UPLO,N,NRHS,AP,IPIV,B,LDB,RCOND,ERRBND,IFAIL)
   IF (IFAIL.EQ.O) THEN
     Print solution, estimate of condition number and approximate
     error bound
     IERR = 0
     WRITE (NOUT, *)
     WRITE (NOUT, *) 'Estimate of condition number'
     WRITE (NOUT, 99999) 1.0D0/RCOND
     WRITE (NOUT, *)
     WRITE (NOUT, *)
       'Estimate of error bound for computed solutions'
     WRITE (NOUT, 99999) ERRBND
   ELSE IF (IFAIL.EQ.N+1) THEN
     Matrix A is numerically singular. Print estimate of
     reciprocal of condition number and solution
     WRITE (NOUT, *)
     WRITE (NOUT, *) 'Estimate of reciprocal of condition number'
     WRITE (NOUT, 99999) RCOND
     WRITE (NOUT, *)
     IERR = 0
     CALL XO4DBF('General',' ',N,NRHS,B,LDB,'Bracketed',' '
                  'Solution','Integer', RLABS,'Integer', CLABS, 80,0,
                 IERR)
   ELSE IF (IFAIL.GT.O .AND. IFAIL.LE.N) THEN
     The upper triangular matrix U is exactly singular. Print
     details of factorization
     WRITE (NOUT, *)
     IERR = 0
     CALL XO4DDF(UPLO,'Non-unit diagonal',N,AP,'Bracketed','',
                  'Details of factorization','Integer',RLABS,
                  'Integer', CLABS, 80, 0, IERR)
     Print pivot indices
     WRITE (NOUT, *)
     WRITE (NOUT, *) 'Pivot indices'
     WRITE (NOUT, 99998) (IPIV(I), I=1, N)
  END IF
ELSE
   WRITE (NOUT,*) 'NMAX and/or NRHSMX too small'
```

[NP3657/21] F04DJF.5

```
END IF
STOP
*
99999 FORMAT (8X,1P,E9.1)
99998 FORMAT ((1X,7111))
```

9.2 Program Data

```
FO4DJF Example Program Data
```

```
4 2 :N and NRHS

(-0.56, 0.12) (-1.54, -2.86) ( 5.32, -1.59) ( 3.80, 0.92) ( -2.83, -0.03) ( -3.52, 0.58) ( -7.86, -2.96) ( 8.86, 1.81) ( 5.14, -0.64) ( -0.39, -0.71) :End matrix A

(-6.43, 19.24) (-4.59, -35.53) ( -0.49, -1.47) ( 6.95, 20.49) (-48.18, 66.00) (-12.08, -27.02) (-55.64, 41.22) (-19.09, -35.97) :End matrix B
```

9.3 Program Results

FO4DJF Example Program Results

```
Solution
```

```
1 ( -4.0000, 3.0000) ( -1.0000, 1.0000)
2 ( 3.0000, -2.0000) ( 3.0000, 2.0000)
3 ( -2.0000, 5.0000) ( 1.0000, -3.0000)
4 ( 1.0000, -1.0000) ( -2.0000, -1.0000)
```

Estimate of condition number 2.1E+01

Estimate of error bound for computed solutions 2.3E-15

F04DJF.6 (last) [NP3657/21]