

# NAG Fortran Library Routine Document

## F04MFF

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

### 1 Purpose

F04MFF updates the solution of the equations  $Tx = b$ , where  $T$  is a real symmetric positive-definite Toeplitz matrix.

### 2 Specification

```
SUBROUTINE F04MFF(N, T, B, X, P, WORK, IFAIL)
INTEGER          N, IFAIL
real            T(0:*), B(*), X(*), P, WORK(*)
```

### 3 Description

This routine solves the equations

$$T_n x_n = b_n,$$

where  $T_n$  is the  $n$  by  $n$  symmetric positive-definite Toeplitz matrix

$$T_n = \begin{pmatrix} \tau_0 & \tau_1 & \tau_2 & \cdots & \tau_{n-1} \\ \tau_1 & \tau_0 & \tau_1 & \cdots & \tau_{n-2} \\ \tau_2 & \tau_1 & \tau_0 & \cdots & \tau_{n-3} \\ \cdot & \cdot & \cdot & & \cdot \\ \tau_{n-1} & \tau_{n-2} & \tau_{n-3} & \cdots & \tau_0 \end{pmatrix}$$

and  $b_n$  is the  $n$  element vector  $b_n = (\beta_1 \beta_2 \dots \beta_n)^T$ , given the solution of the equations

$$T_{n-1} x_{n-1} = b_{n-1}.$$

This routine will normally be used to successively solve the equations

$$T_k x_k = b_k, \quad k = 1, 2, \dots, n.$$

If it is desired to solve the equations for a single value of  $n$ , then routine F04FFF may be called. This routine uses the method of Levinson (see Levinson (1947) and Golub and van Loan (1996), .

### 4 References

- Bunch J R (1985) Stability of methods for solving Toeplitz systems of equations *SIAM J. Sci. Statist. Comput.* **6** 349–364
- Bunch J R (1987) The weak and strong stability of algorithms in numerical linear algebra *Linear Algebra Appl.* **88/89** 49–66
- Cybenko G (1980) The numerical stability of the Levinson–Durbin algorithm for Toeplitz systems of equations *SIAM J. Sci. Statist. Comput.* **1** 303–319
- Golub G H and van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore
- Levinson N (1947) The Weiner RMS error criterion in filter design and prediction *J. Math. Phys.* **25** 261–278

## 5 Parameters

- 1: N – INTEGER *Input*  
*On entry:* the order of the Toeplitz matrix  $T$ .  
*Constraint:*  $N \geq 0$ . When  $N=0$ , then an immediate return is effected.
  
- 2: T(0:\*) – *real* array *Input*  
**Note:** the dimension of the array T must be at least  $\max(1, N)$ .  
*On entry:*  $T(i)$  must contain the values  $\tau_i$ ,  $i = 0, 1, \dots, N-1$ .  
*Constraint:*  $T(0) > 0.0$ . Note that if this is not true, then the Toeplitz matrix cannot be positive-definite.
  
- 3: B(\*) – *real* array *Input*  
**Note:** the dimension of the array B must be at least  $\max(1, N)$ .  
*On entry:* the right-hand side vector  $b_n$ .
  
- 4: X(\*) – *real* array *Input/Output*  
**Note:** the dimension of the array X must be at least  $\max(1, N)$ .  
*On entry:* with  $N > 1$  the  $(n-1)$  elements of the solution vector  $x_{n-1}$  as returned by a previous call to this routine. The element  $X(N)$  need not be specified.  
*On exit:* the solution vector  $x_n$ .
  
- 5: P – *real* *Output*  
*On exit:* the reflection coefficient  $p_{n-1}$ . (See Section 8.)
  
- 6: WORK(\*) – *real* array *Input/Output*  
**Note:** the dimension of the array WORK must be at least  $\max(1, 2 * N - 1)$ .  
*On entry:* with  $N > 2$  the elements of WORK should be as returned from a previous call to F04MFF with  $(N-1)$  as the argument N.  
*On exit:* the first  $(N-1)$  elements of WORK contain the solution to the Yule–Walker equations
 
$$T_{n-1}y_{n-1} = -t_{n-1},$$
 where  $t_{n-1} = (\tau_1 \tau_2 \dots \tau_{n-1})T$ .
  
- 7: IFAIL – INTEGER *Input/Output*  
*On entry:* IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.  
*On exit:* IFAIL = 0 unless the routine detects an error (see Section 6).  
 For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**

## 6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = -1

On entry,  $N < 0$ ,  
or  $T(0) \leq 0.0$ .

IFAIL = 1

The Toeplitz matrix  $T_n$  is not positive-definite to working accuracy. If, on exit, P is close to unity, then  $T_n$  was probably close to being singular.

## 7 Accuracy

The computed solution of the equations certainly satisfies

$$r = T_n x_n - b_n,$$

where  $\|r\|_1$  is approximately bounded by

$$\|r\|_1 \leq c\epsilon C(T_n),$$

$c$  being a modest function of  $n$ ,  $\epsilon$  being the **machine precision** and  $C(T)$  being the condition number of  $T$  with respect to inversion. This bound is almost certainly pessimistic, but it seems unlikely that the method of Levinson is backward stable, so caution should be exercised when  $T_n$  is ill-conditioned. The following bound on  $T_n^{-1}$  holds:

$$\max\left(\frac{1}{\prod_{i=1}^{n-1}(1-p_i^2)}, \frac{1}{\prod_{i=1}^{n-1}(1-p_i)}\right) \leq \|T_n^{-1}\|_1 \leq \prod_{i=1}^{n-1} \left(\frac{1+|p_i|}{1-|p_i|}\right).$$

(See Golub and van Loan (1996).) The norm of  $T_n^{-1}$  may also be estimated using routine F04YCF. For further information on stability issues see Bunch (1985), Bunch (1987), Cybenko (1980) and Golub and van Loan (1996).

## 8 Further Comments

The number of floating-point operations used by this routine is approximately  $8n$ .

If  $y_i$  is the solution of the equations

$$T_i y_i = -(\tau_1 \tau_2 \dots \tau_i)^T,$$

then the reflection coefficient  $p_i$  is defined as the  $i$ th element of  $y_i$ .

## 9 Example

To find the solution of the equations  $T_k x_k = b_k$ ,  $k = 1, 2, 3, 4$ , where

$$T_4 = \begin{pmatrix} 4 & 3 & 2 & 1 \\ 3 & 4 & 3 & 2 \\ 2 & 3 & 4 & 3 \\ 1 & 2 & 3 & 4 \end{pmatrix} \quad \text{and} \quad b_4 = \begin{pmatrix} 1 \\ 1 \\ 1 \\ 1 \end{pmatrix}.$$

### 9.1 Program Text

**Note:** the listing of the example program presented below uses **bold italicised** terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
*      F04MFF Example Program Text
*      Mark 15 Release. NAG Copyright 1991.
*      .. Parameters ..
      INTEGER          NIN, NOUT
      PARAMETER        (NIN=5, NOUT=6)
      INTEGER          NMAX
      PARAMETER        (NMAX=100)
*      .. Local Scalars ..
```

```

      real                                P
      INTEGER                            I, IFAIL, K, N
*    .. Local Arrays ..
      real                                B(NMAX), T(0:NMAX-1), WORK(2*NMAX-1), X(NMAX)
*    .. External Subroutines ..
      EXTERNAL                            F04MFF
*    .. Executable Statements ..
      WRITE (NOUT,*) 'F04MFF Example Program Results'
*    Skip heading in data file
      READ (NIN,*)
      READ (NIN,*) N
      WRITE (NOUT,*)
      IF ((N.LT.0).OR.(N.GT.NMAX)) THEN
         WRITE (NOUT,99999) 'N is out of range. N = ', N
      ELSE
         READ (NIN,*) (T(I),I=0,N-1)
         READ (NIN,*) (B(I),I=1,N)
*
         DO 20 K = 1, N
*
            IFAIL = 0
*
            CALL F04MFF(K,T,B,X,P,WORK,IFAIL)
*
            WRITE (NOUT,*)
            WRITE (NOUT,99999) 'Solution for system of order', K
            WRITE (NOUT,99998) (X(I),I=1,K)
            IF (K.GT.1) THEN
               WRITE (NOUT,*) 'Reflection coefficient'
               WRITE (NOUT,99998) P
            END IF
20      CONTINUE
      END IF
      STOP
*
99999 FORMAT (1X,A,I5)
99998 FORMAT (1X,5F9.4)
      END

```

## 9.2 Program Data

F04MFF Example Program Data

```

4                                :Value of N
4.0  3.0  2.0  1.0              :End of vector T
1.0  1.0  1.0  1.0              :End of vector B

```

## 9.3 Program Results

F04MFF Example Program Results

```

Solution for system of order      1
0.2500

Solution for system of order      2
0.1429  0.1429
Reflection coefficient
-0.7500

Solution for system of order      3
0.1667 -0.0000  0.1667
Reflection coefficient
0.1429

Solution for system of order      4
0.2000 -0.0000  0.0000  0.2000
Reflection coefficient
0.1667

```