

NAG Fortran Library Routine Document

F06GWF (ZSCTR)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F06GWF (ZSCTR) scatters the elements of a sparse complex vector x stored in compressed form, into a complex vector y in full storage form.

2 Specification

```
SUBROUTINE F06GWF (NZ, X, INDX, Y)
  INTEGER          NZ, INDX(*)
  complex*16      X(*), Y(*)
```

The routine may be called by its BLAS name *zsctr*.

3 Description

None.

4 References

None.

5 Parameters

- | | | |
|----|--|---------------|
| 1: | NZ – INTEGER | <i>Input</i> |
| | <i>On entry:</i> the number of elements in the compressed vector x . | |
| 2: | X(*) – complex*16 array | <i>Input</i> |
| | <i>On entry:</i> the compressed vector x . | |
| 3: | INDX(*) – INTEGER array | <i>Input</i> |
| | <i>On entry:</i> the indices of the elements in the compressed vector x . | |
| | <i>Constraint:</i> The indices must be distinct. | |
| 4: | Y(*) – complex*16 array | <i>Output</i> |
| | <i>On exit:</i> the vector y . Only elements corresponding to indices in INDX are altered. | |

6 Error Indicators and Warnings

None.