

NAG Fortran Library Routine Document

F06PMF (DGER)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

F06PMF (DGER) performs the rank-1 update operation

$$A \leftarrow \alpha xy^T + A,$$

where A is an m by n real matrix, x is an m element real vector, y is an n element real vector, and α is a real scalar.

2 Specification

```
SUBROUTINE F06PMF (M, N, ALPHA, X, INCX, Y, INCY, A, LDA)
  INTEGER          M, N, INCX, INCY, LDA
  double precision ALPHA, X(*), Y(*), A(LDA,*)
```

The routine may be called by its BLAS name ***dger***.

3 Description

None.

4 References

None.

5 Parameters

- | | | |
|----|--|--------------|
| 1: | M – INTEGER
<i>On entry:</i> m , the number of rows of the matrix A .
<i>Constraint:</i> $M \geq 0$. | <i>Input</i> |
| 2: | N – INTEGER
<i>On entry:</i> n , the number of columns of the matrix A .
<i>Constraint:</i> $N \geq 0$. | <i>Input</i> |
| 3: | ALPHA – double precision
<i>On entry:</i> the scalar α . | <i>Input</i> |
| 4: | X(*) – double precision array
<i>On entry:</i> the vector x . | <i>Input</i> |
| 5: | INCX – INTEGER
<i>On entry:</i> the increment in the subscripts of X between successive elements of x .
<i>Constraint:</i> $INCX \neq 0$. | <i>Input</i> |

- 6: $Y(*)$ – **double precision** array *Input*
 On entry: the vector y .
- 7: INCY – INTEGER *Input*
 On entry: the increment in the subscripts of Y between successive elements of y .
 Constraint: $\text{INCY} \neq 0$.
- 8: $A(\text{LDA},*)$ – **double precision** array *Input/Output*
 Note: the second dimension of the array A must be at least $\max(1, N)$.
 On entry: the m by n matrix A .
 On exit: the updated matrix A .
- 9: LDA – INTEGER *Input*
 On entry: the first dimension of the array A as declared in the (sub)program from which F06PMF (DGER) is called.
 Constraint: $\text{LDA} \geq \max(1, M)$.

6 Error Indicators and Warnings

None.
