

# NAG Fortran Library Routine Document

## **F06UGF**

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

### 1 Purpose

F06UGF returns, via the function name, the value of the 1-norm, the  $\infty$ -norm, the Frobenius norm, or the maximum absolute value of the elements of a complex  $n$  by  $n$  symmetric matrix, stored in packed form.

### 2 Specification

```
double precision FUNCTION F06UGF (NORM, UPLO, N, AP, WORK)
      INTEGER                         N
      double precision                 WORK(*)
      complex*16                      AP(*)
      CHARACTER*1                      NORM, UPLO
```

### 3 Description

None.

### 4 References

None.

### 5 Parameters

1: NORM – CHARACTER\*1 *Input*

*On entry:* specifies the value to be returned:

- if NORM = '1' or 'O', the 1-norm;
- if NORM = 'I', the  $\infty$ -norm (= the 1-norm for a symmetric matrix);
- if NORM = 'F' or 'E', the Frobenius (or Euclidean) norm;
- if NORM = 'M', the value  $\max_{i,j} |a_{ij}|$  (not a norm).

*Constraint:* NORM = '1', 'O', 'I', 'F', 'E' or 'M'.

2: UPLO – CHARACTER\*1 *Input*

*On entry:* specifies whether the upper or lower triangular part of  $A$  is stored as follows:

- if UPLO = 'U', the upper triangular part of  $A$  is stored;
- if UPLO = 'L', the lower triangular part of  $A$  is stored.

*Constraint:* UPLO = 'U' or 'L'.

3: N – INTEGER *Input*

*On entry:*  $n$ , the order of the matrix  $A$ .

*Constraint:*  $N \geq 0$ .

4: AP(\*) – **complex\*16** array *Input*

**Note:** the dimension of the array AP must be at least  $\max(1, N \times (N + 1)/2)$ .

*On entry:* the  $n$  by  $n$  symmetric matrix  $A$ , packed by columns. More precisely, if  $\text{UPLO} = \text{'U'}$ , the upper triangle of  $A$  must be stored with element  $a_{ij}$  in  $\text{AP}(i + j(j - 1)/2)$  for  $i \leq j$ ; if  $\text{UPLO} = \text{'L'}$ , the lower triangle of  $A$  must be stored with element  $a_{ij}$  in  $\text{AP}(i + (2n - j)(j - 1)/2)$  for  $i \geq j$ .

5: WORK(\*) – **double precision** array *Workspace*

**Note:** the dimension of the array WORK must be at least  $\max(1, N)$  if  $\text{NORM} = \text{'1'}$ ,  $\text{'O'}$  or  $\text{'T'}$  and at least 1 otherwise.

## 6 Error Indicators and Warnings

None.

---