

NAG Fortran Library Routine Document

F07GGF (SPPCON/DPPCON)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

F07GGF (SPPCON/DPPCON) estimates the condition number of a real symmetric positive-definite matrix A , where A has been factorized by F07GDF (SPPTRF/DPPTRF), using packed storage.

2 Specification

```
SUBROUTINE F07GGF(UPLO, N, AP, ANORM, RCOND, WORK, IWORK, INFO)
ENTRY      sppcon (UPLO, N, AP, ANORM, RCOND, WORK, IWORK, INFO)
INTEGER    N, IWORK(*), INFO
real      AP(*), ANORM, RCOND, WORK(*)
CHARACTER*1 UPLO
```

The ENTRY statement enables the routine to be called by its LAPACK name.

3 Description

This routine estimates the condition number (in the 1-norm) of a real symmetric positive-definite matrix A :

$$\kappa_1(A) = \|A\|_1 \|A^{-1}\|_1.$$

Since A is symmetric, $\kappa_1(A) = \kappa_\infty(A) = \|A\|_\infty \|A^{-1}\|_\infty$.

Because $\kappa_1(A)$ is infinite if A is singular, the routine actually returns an estimate of the **reciprocal** of $\kappa_1(A)$.

The routine should be preceded by a call to F06RDF to compute $\|A\|_1$ and a call to F07GDF (SPPTRF/DPPTRF) to compute the Cholesky factorization of A . The routine then uses Higham's implementation of Hager's method (see Higham (1988)) to estimate $\|A^{-1}\|_1$.

4 References

Higham N J (1988) FORTRAN codes for estimating the one-norm of a real or complex matrix, with applications to condition estimation *ACM Trans. Math. Software* **14** 381–396

5 Parameters

1: UPLO – CHARACTER*1 *Input*

On entry: indicates whether A has been factorized as $U^T U$ or LL^T as follows:

if UPLO = 'U', $A = U^T U$, where U is upper triangular;

if UPLO = 'L', $A = LL^T$, where L is lower triangular.

Constraint: UPLO = 'U' or 'L'.

2: N – INTEGER *Input*

On entry: n , the order of the matrix A .

Constraint: $N \geq 0$.

- 3: AP(*) – *real* array *Input*
Note: the dimension of the array AP must be at least $\max(1, N * (N + 1) / 2)$.
On entry: the Cholesky factor of A stored in packed form, as returned by F07GDF (SPPTRF/DPPTRF).
- 4: ANORM – *real* *Input*
On entry: the 1-norm of the **original** matrix A , which may be computed by calling F06RDF. ANORM must be computed either **before** calling F07GDF (SPPTRF/DPPTRF) or else from a copy of the original matrix A .
Constraint: $ANORM \geq 0.0$.
- 5: RCOND – *real* *Output*
On exit: an estimate of the reciprocal of the condition number of A . RCOND is set to zero if exact singularity is detected or the estimate underflows. If RCOND is less than **machine precision**, A is singular to working precision.
- 6: WORK(*) – *real* array *Workspace*
Note: the dimension of the array WORK must be at least $\max(1, 3 * N)$.
- 7: IWORK(*) – INTEGER array *Workspace*
Note: the dimension of the array IWORK must be at least $\max(1, N)$.
- 8: INFO – INTEGER *Output*
On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

Errors or warnings detected by the routine:

INFO < 0

If $INFO = -i$, the i th parameter had an illegal value. An explanatory message is output, and execution of the program is terminated.

7 Accuracy

The computed estimate RCOND is never less than the true value ρ , and in practice is nearly always less than 10ρ , although examples can be constructed where RCOND is much larger.

8 Further Comments

A call to this routine involves solving a number of systems of linear equations of the form $Ax = b$; the number is usually 4 or 5 and never more than 11. Each solution involves approximately $2n^2$ floating-point operations but takes considerably longer than a call to F07GEF (SPPTRS/DPPTRS) with 1 right-hand side, because extra care is taken to avoid overflow when A is approximately singular.

The complex analogue of this routine is F07GUF (CPPCON/ZPPCON).

9 Example

To estimate the condition number in the 1-norm (or infinity-norm) of the matrix A , where

$$A = \begin{pmatrix} 4.16 & -3.12 & 0.56 & -0.10 \\ -3.12 & 5.03 & -0.83 & 1.18 \\ 0.56 & -0.83 & 0.76 & 0.34 \\ -0.10 & 1.18 & 0.34 & 1.18 \end{pmatrix}.$$

Here A is symmetric positive-definite, stored in packed form, and must first be factorized by F07GDF (SPPTRF/DPPTFR). The true condition number in the 1-norm is 97.32.

9.1 Program Text

Note: the listing of the example program presented below uses *bold italicised* terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
*      F07GGF Example Program Text
*      Mark 15 Release. NAG Copyright 1991.
*      .. Parameters ..
      INTEGER          NIN, NOUT
      PARAMETER        (NIN=5,NOUT=6)
      INTEGER          NMAX
      PARAMETER        (NMAX=8)
*      .. Local Scalars ..
      real             ANORM, RCOND
      INTEGER          I, INFO, J, N
      CHARACTER        UPLO
*      .. Local Arrays ..
      real             AP(NMAX*(NMAX+1)/2), WORK(3*NMAX)
      INTEGER          IWORK(NMAX)
*      .. External Functions ..
      real             F06RDF, X02AJF
      EXTERNAL         F06RDF, X02AJF
*      .. External Subroutines ..
      EXTERNAL         sppcon, spptrf
*      .. Executable Statements ..
      WRITE (NOUT,*) 'F07GGF Example Program Results'
*      Skip heading in data file
      READ (NIN,*)
      READ (NIN,*) N
      IF (N.LE.NMAX) THEN
*
*          Read A from data file
*
*          READ (NIN,*) UPLO
*          IF (UPLO.EQ.'U') THEN
*              READ (NIN,*) ((AP(I+J*(J-1)/2),J=I,N),I=1,N)
*          ELSE IF (UPLO.EQ.'L') THEN
*              READ (NIN,*) ((AP(I+(2*N-J)*(J-1)/2),J=1,I),I=1,N)
*          END IF
*
*          Compute norm of A
*
*          ANORM = F06RDF('1-norm',UPLO,N,AP,WORK)
*
*          Factorize A
*
*          CALL spptrf(UPLO,N,AP,INFO)
*
*          WRITE (NOUT,*)
*          IF (INFO.EQ.0) THEN
*
*              Estimate condition number
*
*              CALL sppcon(UPLO,N,AP,ANORM,RCOND,WORK,IWORK,INFO)
*
*              IF (RCOND.GE.X02AJF()) THEN
```

```

      +      WRITE (NOUT,99999) 'Estimate of condition number =',
            1.0e0/RCOND
      ELSE
        WRITE (NOUT,*) 'A is singular to working precision'
      END IF
    ELSE
      WRITE (NOUT,*) 'A is not positive-definite'
    END IF
  END IF
STOP
*
99999 FORMAT (1X,A,1P,e10.2)
END

```

9.2 Program Data

F07GGF Example Program Data

4					:Value of N
'L'					:Value of UPLO
4.16					
-3.12	5.03				
0.56	-0.83	0.76			
-0.10	1.18	0.34	1.18		:End of matrix A

9.3 Program Results

F07GGF Example Program Results

Estimate of condition number = 9.73E+01
