

NAG Fortran Library Routine Document

G13DBF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

G13DBF calculates the multivariate partial autocorrelation function of a multivariate time series.

2 Specification

```
SUBROUTINE G13DBF(CO, C, NSM, NS, NL, NK, P, V0, V, D, DB, W, WB, NVP,
1                   WA, IWA, IFAIL)
      INTEGER          NSM, NS, NL, NK, NVP, IWA, IFAIL
      real             CO(NSM,NS), C(NSM,NSM,NL), P(NK), V0, V(NK),
1                   D(NSM,NSM,NK), DB(NSM,NS), W(NSM,NSM,NK),
2                   WB(NSM,NSM,NK), WA(IWA)
```

3 Description

The input is a set of lagged autocovariance matrices $C_0, C_1, C_2, \dots, C_K$. These will generally be sample values such as are obtained from a multivariate time series using G13DMF. If sample autocorrelation matrices are used as input, then the output will be relevant to the original series scaled by their standard deviations. If these autocorrelation matrices are produced by G13DMF, the user must replace the diagonal elements of C_0 (otherwise used to hold the series variances) by 1.

The main calculation is the recursive determination of the coefficients in the finite lag (forward) prediction equation

$$x_t = \Phi_{k,1}x_{t-1} + \cdots + \Phi_{k,k}x_{t-k} + e_{k,t}$$

and the associated backward prediction equation

$$x_{t-k-1} = \Psi_{k,1}x_{t-k} + \cdots + \Psi_{k,k}x_{t-1} + f_{k,t}$$

together with the covariance matrices D_k of $e_{k,t}$ and G_k of $f_{k,t}$.

The recursive cycle, by which the order of the prediction equation is extended from k to $k+1$, is to calculate

$$M_{k+1} = C'_{k+1} - \Phi_{k,1}C'_k - \cdots - \Phi_{k,k}C'_1 \quad (1)$$

then $\Phi_{k+1,k+1} = M_{k+1}D_k^{-1}$, $\Psi_{k+1,k+1} = M'_{k+1}G_k^{-1}$

from which

$$\Phi_{k+1,j} = \Phi_{k,j} - \Phi_{k+1,k+1}\Psi_{k,k+1-j}, \quad j = 1, 2, \dots, k \quad (2)$$

and

$$\Psi_{k+1,j} = \Psi_{k,j} - \Psi_{k+1,k+1}\Phi_{k,k+1-j}, \quad j = 1, 2, \dots, k. \quad (3)$$

Finally, $D_{k+1} = D_k - M_{k+1}\Phi'_{k+1,k+1}$, and $G_{k+1} = G_k - M'_{k+1}\Psi'_{k+1,k+1}$.

(Here ' denotes the transpose of a matrix.)

The cycle is initialised by taking (for $k = 0$)

$$D_0 = G_0 = C_0.$$

In the step from $k = 0$ to 1, the above equations contain redundant terms and simplify. Thus (1) becomes $M_1 = C'_1$ and neither (2) or (3) are needed.

Quantities useful in assessing the effectiveness of the prediction equation are generalized variance ratios

$$v_k = \det D_k / \det C_0, \quad k = 1, 2, \dots$$

and multiple squared partial autocorrelations

$$p_k^2 = 1 - v_k / v_{k-1}.$$

4 References

Akaike H (1971) Autoregressive model fitting for control *Ann. Inst. Statist. Math.* **23** 163–180

Whittle P (1963) On the fitting of multivariate autoregressions and the approximate canonical factorization of a spectral density matrix *Biometrika* **50** 129–134

5 Parameters

- | | | |
|----|---|---------------|
| 1: | C0(NSM,NS) – real array | <i>Input</i> |
| | <i>On entry:</i> contains the zero lag cross covariances between the NS series. C0 is assumed to be symmetric (upper triangle only is used). | |
| 2: | C(NSM,NSM,NL) – real array | <i>Input</i> |
| | <i>On entry:</i> contains the cross covariances at lags 1 to NL. $C(i,j,k)$ must contain the cross covariance, c_{ijk} , of series i and series j at lag k . Series j leads series i . | |
| 3: | NSM – INTEGER | <i>Input</i> |
| | <i>On entry:</i> the first dimension of arrays C0 and DB and the first and second dimension of arrays C, D, W and WB as declared in the (sub)program from which G13DBF is called. | |
| | <i>Constraint:</i> $NSM \geq \max(NS, 1)$. | |
| 4: | NS – INTEGER | <i>Input</i> |
| | <i>On entry:</i> the number of time series whose cross covariances are supplied in C and C0. | |
| | <i>Constraint:</i> $NS \geq 1$. | |
| 5: | NL – INTEGER | <i>Input</i> |
| | <i>On entry:</i> the maximum lag, K , for which cross covariances are supplied in C. | |
| | <i>Constraint:</i> $NL \geq 1$. | |
| 6: | NK – INTEGER | <i>Input</i> |
| | <i>On entry:</i> the number of lags to which partial auto-correlations are to be calculated. | |
| | <i>Constraint:</i> $1 \leq NK \leq NL$. | |
| 7: | P(NK) – real array | <i>Output</i> |
| | <i>On exit:</i> the multiple squared partial autocorrelations from lags 1 to NVP; that is, $P(k)$ contains p_k^2 , for $k = 1, 2, \dots, NVP$. For lags $NVP + 1$ to NK the elements of P are set to zero. | |
| 8: | V0 – real | <i>Output</i> |
| | <i>On exit:</i> the lag zero prediction error variance (equal to the determinant of C0). | |
| 9: | V(NK) – real array | <i>Output</i> |
| | <i>On exit:</i> the prediction error variance ratios from lags 1 to NVP; that is, $V(k)$ contains v_k , for $k = 1, 2, \dots, NVP$. For lags $NVP + 1$ to NK the elements of V are set to zero. | |

10:	D(NSM,NSM,NK) – real array	<i>Output</i>
<i>On exit:</i> the prediction error variance matrices at lags 1 to NVP.		
Element (i, j, k) of D contains the prediction error covariance of series i and series j at lag k , for $k = 1, 2, \dots, \text{NVP}$. Series j leads series i ; that is, the (i, j) th element of D_k . For lags $\text{NVP} + 1$ to NK the elements of D are set to zero.		
11:	DB(NSM,NS) – real array	<i>Output</i>
<i>On exit:</i> the backward prediction error variance matrix at lag NVP.		
DB(i, j) contains the backward prediction error covariance of series i and series j ; that is, the (i, j) th element of the G_k , where $k = \text{NVP}$.		
12:	W(NSM,NSM,NK) – real array	<i>Output</i>
<i>On exit:</i> the prediction coefficient matrices at lags 1 to NVP.		
W(i, j, l) contains the j th prediction coefficient of series i at lag l ; that is, the (i, j) th element of Φ_{kl} , where $k = \text{NVP}$, for $l = 1, 2, \dots, \text{NVP}$. For lags $\text{NVP} + 1$ to NK the elements of W are set to zero.		
13:	WB(NSM,NSM,NK) – real array	<i>Output</i>
<i>On exit:</i> the backward prediction coefficient matrices at lags 1 to NVP.		
WB(i, j, l) contains the j th backward prediction coefficient of series i at lag l ; that is, the (i, j) th element of Ψ_{kl} , where $k = \text{NVP}$, for $l = 1, 2, \dots, \text{NVP}$. For lags $\text{NVP} + 1$ to NK the elements of WB are set to zero.		
14:	NVP – INTEGER	<i>Output</i>
<i>On exit:</i> the maximum lag for which calculation of P, V, D, DB, W and WB was successful. If the routine completes successfully NVP will equal NK.		
15:	WA(IWA) – real array	<i>Workspace</i>
16:	IWA – INTEGER	<i>Input</i>
<i>On entry:</i> the dimension of the array WA as declared in the (sub)program from which G13DBF is called.		
<i>Constraint:</i> IWA $\geq (2 \times \text{NS} + 1) \times \text{NS}$.		
17:	IFAIL – INTEGER	<i>Input/Output</i>
<i>On entry:</i> IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.		
<i>On exit:</i> IFAIL = 0 unless the routine detects an error (see Section 6).		
For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.		

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

On entry, NSM < 1,
or NS < 1,

or $NS > NSM$,
 or $NL < 1$,
 or $NK < 1$,
 or $NK > NL$,
 or $IWA < (2 \times NS + 1) \times NS$.

IFAIL = 2

C_0 is not positive-definite.

V_0, V, P, D, DB, W, WB and NVP are set to zero.

IFAIL = 3

At lag $k = NVP + 1 \leq NK$, D_k was found not to be positive-definite. Up to lag NVP , V_0, V, P, D, W and WB contain the values calculated so far and from lag $NVP + 1$ to lag NK the matrices contain zero. DB contains the backward prediction coefficients for lag NVP .

7 Accuracy

The conditioning of the problem depends on the prediction error variance ratios. Very small values of these may indicate loss of accuracy in the computations.

8 Further Comments

The time taken by the routine is roughly proportional to $NK^2 \times NS^3$.

9 Example

The example program reads the autocovariance matrices for four series from lag 0 to 5. It calls G13DBF to calculate the multivariate partial autocorrelation function and other related matrices of statistics up to lag 3. It prints the results.

9.1 Program Text

Note: the listing of the example program presented below uses ***bold italicised*** terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```

*      G13DBF Example Program Text
*      Mark 14 Revised. NAG Copyright 1989.
*      .. Parameters ..
  INTEGER          NSMAX, NSM, NLMAX, NKMAX, IWA
  PARAMETER        (NSMAX=6, NSM=NSMAX, NLMAX=5, NKMAX=NLMAX,
+                  IWA=(2*NSMAX+1)*NSMAX)
  INTEGER          NIN, NOUT
  PARAMETER        (NIN=5, NOUT=6)
*      .. Local Scalars ..
real           VO
  INTEGER          I, I1, IFAIL, J, J1, K, NK, NL, NS, NVP
*      .. Local Arrays ..
real           C(NSM,NSM,NLMAX), CO(NSM,NSMAX),
+                  D(NSM,NSM,NKMAX), DB(NSM,NSMAX), P(NKMAX),
+                  V(NKMAX), W(NSM,NSM,NKMAX), WA(IWA),
+                  WB(NSM,NSM,NKMAX)
*      .. External Subroutines ..
  EXTERNAL         G13DBF
*      .. Executable Statements ..
  WRITE (NOUT,*) 'G13DBF Example Program Results'
*      Skip heading in data file
  READ (NIN,*)
*      Read series length, and numbers of lags
  READ (NIN,*) NS, NL, NK
  IF (NS.GT.0 .AND. NS.LE.NSMAX .AND. NL.GT.0 .AND. NL.LE.
+      NLMAX .AND. NK.GT.0 .AND. NK.LE.NKMAX) THEN

```

```

*      Read autocovariances
READ (NIN,*) ((CO(I,J),J=1,NS),I=1,NS)
READ (NIN,*) (((C(I,J,K),J=1,NS),I=1,NS),K=1,NL)
*      Call routine to calculate multivariate partial autocorrelation
*      function
IFAIL = 1
*
CALL G13DBF(CO,C,NSM,NS,NL,NK,P,VO,V,D,DB,W,WB,NVP,WA,IWA,
             IFAIL)
*
WRITE (NOUT,*)
IF (IFAIL.NE.0) THEN
    WRITE (NOUT,99999) 'G13DBF fails. IFAIL =', IFAIL
    WRITE (NOUT,*)
END IF
IF (IFAIL.EQ.0 .OR. IFAIL.EQ.3) THEN
    WRITE (NOUT,99998) 'Number of valid parameters =', NVP
    WRITE (NOUT,*)
    WRITE (NOUT,*) 'Multivariate partial autocorrelations'
    WRITE (NOUT,99997) (P(I1),I1=1,NK)
    WRITE (NOUT,*)
    WRITE (NOUT,*)
    WRITE (NOUT,*) 'Zero lag predictor error variance determinant'
    WRITE (NOUT,*) 'followed by error variance ratios'
    WRITE (NOUT,99997) VO, (V(I1),I1=1,NK)
    WRITE (NOUT,*)
    WRITE (NOUT,*) 'Prediction error variances'
DO 40 K = 1, NK
    WRITE (NOUT,*)
    WRITE (NOUT,99996) 'Lag =', K
    DO 20 I = 1, NS
        WRITE (NOUT,99997) (D(I,J1,K),J1=1,NS)
CONTINUE
20
40
CONTINUE
WRITE (NOUT,*)
WRITE (NOUT,*) 'Last backward prediction error variances'
WRITE (NOUT,*)
WRITE (NOUT,99996) 'Lag =', NVP
DO 60 I = 1, NS
    WRITE (NOUT,99997) (DB(I,J1),J1=1,NS)
CONTINUE
60
CONTINUE
WRITE (NOUT,*)
WRITE (NOUT,*) 'Prediction coefficients'
DO 100 K = 1, NK
    WRITE (NOUT,*)
    WRITE (NOUT,99996) 'Lag =', K
    DO 80 I = 1, NS
        WRITE (NOUT,99997) (W(I,J1,K),J1=1,NS)
CONTINUE
80
CONTINUE
100
CONTINUE
WRITE (NOUT,*)
WRITE (NOUT,*) 'Backward prediction coefficients'
DO 140 K = 1, NK
    WRITE (NOUT,*)
    WRITE (NOUT,99996) 'Lag =', K
    DO 120 I = 1, NS
        WRITE (NOUT,99997) (WB(I,J1,K),J1=1,NS)
CONTINUE
120
CONTINUE
140
CONTINUE
END IF
END IF
STOP
*
99999 FORMAT (1X,A,I3)
99998 FORMAT (1X,A,I10)
99997 FORMAT (1X,5F12.5)
99996 FORMAT (1X,A,I5)
END

```

9.2 Program Data

```
G13DBF Example Program Data
      4      5      3    500
.10900E-01 -.77917E-02 .13004E-02 .12654E-02
-.77917E-02 .57040E-01 .24180E-02 .14409E-01
.13004E-02 .24180E-02 .43960E-01 -.21421E-01
.12654E-02 .14409E-01 -.21421E-01 .72289E-01
.45889E-02 .46510E-03 -.13275E-03 .77531E-02
-.24419E-02 -.11667E-01 -.21956E-01 -.45803E-02
.11080E-02 -.80479E-02 .13621E-01 -.85868E-02
-.50614E-03 .14045E-01 -.10087E-02 .12269E-01
.18652E-02 -.64389E-02 .88307E-02 -.24808E-02
-.11865E-01 .72367E-02 -.19802E-01 .59069E-02
-.80307E-02 .14306E-01 .14546E-01 .13510E-01
-.21791E-02 -.29528E-01 -.15887E-01 .88308E-03
-.80550E-04 -.37759E-02 .75463E-02 -.42276E-02
.41447E-02 -.37987E-02 .19332E-02 -.17564E-01
-.10582E-01 .67733E-02 .69832E-02 .61747E-02
.41352E-02 -.16013E-01 .17043E-01 -.13412E-01
.76079E-03 -.10134E-02 .11870E-01 -.41651E-02
.36014E-02 -.36375E-02 -.25571E-01 .50218E-02
-.13924E-01 .11718E-01 -.59088E-02 .59297E-02
.10739E-01 -.14571E-01 .13816E-01 -.12588E-01
-.64365E-03 -.44556E-02 .51334E-02 .71587E-03
.63617E-02 .15217E-03 .27270E-02 -.22261E-02
-.85855E-02 .14468E-02 -.28698E-02 .44384E-02
.68339E-02 -.21790E-02 .13759E-01 .28217E-03
```

9.3 Program Results

G13DBF Example Program Results

Number of valid parameters = 3

Multivariate partial autocorrelations
0.64498 0.92669 0.84300

Zero lag predictor error variance determinant
followed by error variance ratios
0.00000 0.35502 0.02603 0.00409

Prediction error variances

Lag = 1
0.00811 -0.00511 0.00159 -0.00029
-0.00511 0.04089 0.00757 0.01843
0.00159 0.00757 0.03834 -0.01894
-0.00029 0.01843 -0.01894 0.06760

Lag = 2
0.00354 -0.00087 -0.00075 -0.00105
-0.00087 0.01946 0.00535 0.00566
-0.00075 0.00535 0.01900 -0.01071
-0.00105 0.00566 -0.01071 0.04058

Lag = 3
0.00301 -0.00087 -0.00054 0.00065
-0.00087 0.01824 0.00872 0.00247
-0.00054 0.00872 0.00935 -0.00216
0.00065 0.00247 -0.00216 0.02254

Last backward prediction error variances

Lag = 3
0.00331 -0.00392 -0.00106 0.00592
-0.00392 0.01890 0.00348 -0.00330
-0.00106 0.00348 0.01003 -0.01054
0.00592 -0.00330 -0.01054 0.03336

Prediction coefficients

Lag = 1

0.81861	0.23399	-0.17097	0.09256
0.06738	-0.48720	-0.14064	0.04295
0.15036	0.11924	-0.36725	-0.42092
-0.70971	0.02998	0.59779	0.34610

Lag = 2

-0.34049	-0.13370	0.40610	-0.02183
-1.27574	-0.13591	-0.65779	-0.11267
-0.45439	0.19379	0.63420	0.33920
-0.43237	-0.54848	-0.62897	0.16670

Lag = 3

0.16437	0.13858	0.01290	0.03463
0.39291	0.07407	-0.08802	-0.15361
-1.29240	-0.24489	0.30235	0.39442
0.89768	-0.39040	0.25151	-0.28304

Backward prediction coefficients

Lag = 1

0.41541	0.06149	0.15319	0.05079
0.12370	-0.26471	-0.22721	0.48503
-0.86933	-0.47373	0.37924	0.13814
1.30779	-0.09178	-1.45398	-0.21967

Lag = 2

-0.06740	-0.12255	-0.13673	-0.09730
-1.24801	0.03090	0.51706	-0.28925
0.98045	-0.20194	0.16307	-0.10869
-1.68389	-0.74589	0.52900	0.41580

Lag = 3

0.03794	0.10491	-0.21635	0.08015
0.75392	0.22603	-0.25661	-0.47450
-0.00338	0.05636	-0.08818	0.12723
0.55022	-0.41232	0.71649	-0.14565
